

Printing date 19.11.2018

Version number 4

Revision: 19.11.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Polimar Seal
- \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- SU19 Building and construction work
- Application of the substance / the mixture Acrylic sealant
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: IKO Europe nv d'Herbouvillekaai 80 B-2020 Antwerpen Belgium Tel.: +32 (0)3 248 30 00 E-mail: sds.europe@iko.com

· Further information obtainable from:

National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24; National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.

• **1.4 Emergency telephone number:** United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111 Ireland National Poisons Information Centre Tel: +353 1 8092566 Emergency call only for healthcare professionals

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

- · Classification according to Regulation (EC) No 1272/2008
- Flam. Liq. 3 H226 Flammable liquid and vapour.
- STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

 Hazard-determining components of labelling: benzotriazole derivatives sebacate derivatives 2-methoxy-1-methylethyl acetate

(Contd. on page 2)



Printing date 19.11.2018

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

(Contd. of page 1) · Hazard statements H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. P261 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · UFI : 8XJM-08A9-D00M-6URU

• Additional information: May cause an allergic reaction.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	25-40%
CAS: 41556-26-7	Bis(1,2,,2,6,6-pentamethyl-4-piperidyl)sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.3-0.4%
CAS: 82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.3-0.4%
CAS: 104810-48-2 ELINCS: 400-830-7	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω- hydroxy- Aquatic Chronic 2, H411 Skin Sens. 1, H317	0.3-0.4%
CAS: 104810-47-1	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3- (2H- benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1-oxopropoxy]- Aquatic Chronic 2, H411 Skin Sens. 1, H317	≥0.25-<0.39

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

⁻ GB

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

Printing date 19.11.2018

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Not applicable.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB



(Contd. of page 2)

Revision: 19.11.2018

Trade name: Polimar Seal

(Contd. of page 3)
· 8.1 Control parameters
 Ingredients with limit values that require monitoring at the workplace:
CAS: 108-65-6 2-methoxy-1-methylethyl acetate
WEL Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
· Additional information: The lists valid during the making were used as basis.
· 8.2 Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
Respiratory protection: Not required.
Protection of hands: Solvent resistant gloves
 Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· Eye protection:
Tightly sealed goggles

• 9.1 Information on basic physical	l and chemical properties
· Appearance: Form:	Viscous
Colour:	Dark grey
· Odour:	Characteristic
· pH-value:	Not determined.
 Change in condition Initial boiling point and boiling Flash point: 	range: 146 °C 44 °C
· Ignition temperature:	315 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %



Printing date 19.11.2018

Version number 4

number 4



Printing date 19.11.2018

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

	(Cor	td. of page 4)
 Vapour pressure at 20 °C: 	3.4 hPa	
 Density at 20 °C: 	1.3 g/cm ³	
 Solubility in / Miscibility with 		
water:	Insoluble.	
· organic solvents:	Miscible with many organic solvents.	
· Viscosity:	, c	
Dynamic at 20 °C:	19000 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC (EC)	VOC limit value (cat A/i) 500 g/L 2010.	
	Product contains 450 g/L.	
 9.2 Other information 	No further information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- \cdot 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >325 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

Primary irritant effect:

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Splashes in the eyes may cause irritation and reversible local damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. of page 4)

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

 \cdot Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG	UN1263
14.2 UN proper shipping name	
ADR	exemption according 2.2.3.1.5.
	UN 1263, Paint related material, 3, III, (D/E)
IMDG	UN 1263, Paint related material, 3, III, (44°C c.c.)
	"Transport in accordance with 2.3.2.5 of the IMD0 code"
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.



Printing date 19.11.2018



Printing date 19.11.2018

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

	(Contd. of page 6
· 14.4 Packing group · ADR	111
 · 14.5 Environmental hazards: · Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
 14.7 Transport in bulk according to Annex Marpol and the IBC Code 	II of Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
• Tunnel restriction code • UN "Model Regulation":	D/E UN1263, PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57 This product does not contain any SVHC's.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

· Relevant phrases

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 8)

•

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.11.2018

Version number 4

Revision: 19.11.2018

Trade name: Polimar Seal

	(Contd. of page 7
Contact: sds.europe@iko.com	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de Concerning the International Transport of Dangerous Goods by Rail)	e fer (Regulation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreeme International Carriage of Dangerous Goods by Road)	ent concerning th
MDG: International Maritime Code for Dangerous Goods	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	