SAFETY DATA SHEET ACCORDING TO REGULATION (EC) 1907/2006

Product name: G & B Acetone

Creation date: 16.07.2019, Revision: 02.03.2023, version: 2.1



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name G & B Acetone

Name: acetone (CAS: 67-64-1, EC: 200-662-2, Index: 606-001-00-8)

REACH Registration number: 01-2119471330-49

IIFI:

GM00-E0GJ-800K-1KHP



https://my.chemius.net/p/q4SWq6/en/pd/e4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Solvent.

Uses advised against

Do not use for purposes other than those prescribed.

1.3 Details of the supplier of the safety data sheet

Supplier

G&B Northwest Ltd Giants Hall Farm WN6 8RY Wigan, United Kingdom +44 (0)1942 518150 enquiries@gandbnw.co.uk

1.4 Emergency Telephone Number

Emergency

112

Supplier

+44 (0)1942 518150 Mon-Friday 8.30am – 4.30pm

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 2; H225 Highly flammable liquid and vapour.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: DANGER

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours/spray.

P264 Wash hands, forearms and exposed areas thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use appropriate media to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulation.

Contains:

acetone

2.3 Other hazards

PBT/vPvB

No information.

Endocrine disrupting properties

No information.

Additional information

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The components in this formulation do not meet the criteria for classification as PBT.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	≤ 100	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	/	/

3.2 Mixtures

For substances see 3.1.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Obtain professional medical help!

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! If vomiting occurs, the patient should hold the head lower than the hips, because it reduces the possibility of aspiration. Rinse mouth and drink plenty of water (only if the person is conscious). Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Vapours may cause drowsiness and dizziness. Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

Following skin contact

Repeated exposure may cause dry skin or cracked skin. Contact with skin may cause irritation (redness, itching).

Following eye contact

Redness, tearing, pain.

Following ingestion

May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

4.3 Indication of any immediate medical attention and special treatment needed

Have eye wash facilities in place close to the operators' work area to provide immediate first aid prior to medical attention. Severe cases of eye contact and ingestion should receive medical attention immediately.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture. In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training. In case of fire evacuate the area. Prolonged heating can cause an explosion. Fight fire from a reasonable distance.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Take precautionary measures against static discharges. Prevent accumulation of vapours - vapours and air can form explosive mixtures. Vapours can accumulate in low-lying areas.

Emergency procedures

Evacuate the danger zone. Evacuate personnel. No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing. In the event of fire and/or explosion do not breathe fumes.

For emergency responders

During intervention, use personal protective equipment (Section 8).

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Prevent release into the sewer, water, basements or confined areas. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Make sure the leakage site is well aired. Use spark-proof tools. Dispose in accordance with applicable regulations (see Section 13).

OTHER INFORMATION

See Section 7: safe handling. See Section 11 for additional information on health hazards. See Section 12: ECOLOGICAL INFORMATION.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Take precautionary measures against static discharges. Ensure proper grounding of the equipment. Keep away from sources of ignition - no smoking. Use spark-proof tools. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air. In order to avoid the risk of fires and explosions, never use compressed air when handling. Empty containers may contain flammable or explosive vapours.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8. In case of insufficient ventilation, wear suitable respiratory protection equipment. Avoid exposure - obtain special instructions before using. Refer to instructions on label and regulations for safety and health at work. Regular cleaning of equipment, work area and clothing is recommended.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Store in accordance with local regulations. Keep in a cool, dry and well ventilated place. Keep away from heat and sources of ignition. Keep away from food, drink and animal feeding stuffs. Keep away from incompatible products (see section 10).

Packaging materials

No information.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers. The empty containers contain the residues of the preparation and therefore can also pose a risk.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)

Recommendations

See identified uses in Section 1.2.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

Name mg/m³ ml/m³	, 3	Short-term value ml/m ³	Remark	Biological Tolerance Values
------------------	-----	---------------------------------------	--------	--------------------------------

acetone	1780	750	2375	1000	India; source: Ministry of Labour and Employment, Permissible Levels of Certain Chemical substances in work environment	/
Acetone (67-64-1)	1210	500	3620	1500	/	/

Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Туре	Exposure route	exp. frequency	Remark	value
acetone	Worker	inhalation	long term systemic effects	/	1210 mg/m³
acetone	Worker	inhalation	short term local effects	/	2420 mg/m³
acetone	Worker	dermal	long term systemic effects	/	186 mg/kg bw/day
acetone	Consumer	inhalation	long term systemic effects	/	200 mg/m³
acetone	Consumer	dermal	long term systemic effects	/	62 mg/kg bw/day
acetone	Consumer	oral	long term systemic effects	/	62 mg/kg bw/day

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
acetone	fresh water	/	10.6 mg/L
acetone	marine water	/	1.06 mg/L
acetone	water treatment plant	/	100 mg/L
acetone	fresh water sediment	dry weight	30.4 mg/kg
acetone	marine water sediment	dry weight	3.04 mg/kg
acetone	soil	dry weight	33.3 mg/kg

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Appropriate technical measures to reduce exposure of workers must be chosen depending on the specific use of the product and the resulting risk of exposure at the workplace.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Keep eyewash bottles or personal eyewash units available at the workplace.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Wear tight fitting protective goggles and/or face protection (EN 166).

Hand protection

Protective gloves (EN 374). The penetration time is determined by the protective glove manufacturer and must be observed. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Wash hands after every use.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber	0.3 mm	8 h	/

Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). Immediately wash contaminated clothing before reuse.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Protective masks (EN 136) or half masks (EN 140) with filter A (EN 14387). Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

colourless

Odour

pungent

Important health, safety and environmental information

Odour threshold	13 ppm
Melting point/Freezing point	No information.
Boiling point or initial boiling point and boiling range	No information.
Flammability	No information.
Lower and upper explosion limit	2 — 13 vol %
Flash point	-16.99 °C (closed cup)
Auto-ignition temperature	465 °C
Decomposition temperature	No information.
рН	No information.
Viscosity	No information.
Solubility	Water: miscible

Partition coefficient	Log Pow: -0.24
Vapour pressure	433.3 hPa at 39.5 °C 245.3 hPa at 20 °C
Density and/or relative density	Density: 0.791 g/cm ³ at 25 °C
Relative vapour density	No information.
Particle characteristics	No information.

9.2 OTHER INFORMATION

plosive properties	No information.	
--------------------	-----------------	--

Other information

Surface tension: 23.2 mN/m at 20.0°C.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. Take precautionary measures against static discharges. Avoid contact with incompatible materials.

10.5 Incompatible materials

Reducing agents. Bases.

Oxidants.

Acetone reacts violently with phosphorous oxychloride.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
 - (a) Acute toxicity

For components

Name	Exposure route	Туре	Species	Time	value	Method	Remark	

acetone	oral	LD ₅₀	rat	/	5800 mg/kg	/	Behavioural: Altered sleep time, tremor, headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
acetone	inhalation	LD ₅₀	rat	8 h	50100 mg/m ³	/	Drowsiness, Dizziness, Unconciousness
acetone	dermal	LD ₅₀	guinea pig	/	7426 mg/kg	/	/

Additional information

The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
acetone	rabbit	24 h	Mild irritating.	/	/

Additional information

The product is not classified as irritating to the skin.

(c) Serious eye damage/irritation

For components

Name	Exposure route	Species	Time	result	Method	Remark
acetone	/	rabbit	24 h	Irritating.	/	/

Additional information

Causes serious eye irritation.

(d) Respiratory or skin sensitisation

For components

Name	Exposure route	Species	Time	result	Method	Remark
acetone	dermal	guinea pig	/	Non sensitising.	/	/

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

For components

Name	Exposure route	Туре	Species	Time	Exposure	organ	value	result	Method	Remark
acetone	-	-	/	/	/	/	/	May cause drowsiness or dizziness.	/	/

Additional information

May cause drowsiness or dizziness.

(i) STOT-repeated exposure

No information.

Additional information

Repeated exposure may cause skin dryness or cracking.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

Symptoms related to the physical, chemical and toxicological characteristics

No information.

Interactive effects

No information.

11.2 Information on other hazards

Endocrine disrupting properties

No information.

Other information

No information.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

Nar	me	Туре	value	Exposure time	Species	organism	Method	Remark
ace	etone	LC ₅₀	5540 mg/L	96 h	fish	Oncorhynchus mykiss	/	/
ace	tone	LC ₅₀	8800 mg/L	48 h	crustacea	Daphnia magna	/	1

Chronic (long-term) toxicity

No information.

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Туре	Rate	Time	Evaluation	Method	Remark
acetone	biodegradability	91 %	/	rapidly biodegradable	OECD 301 B	/

12.3 Bioaccumulative potential

Partition coefficient

For product

Media	value	Temperature °C	рН	Concentration	Method
Log Pow	-0.24	/	/	/	/

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
acetone	-	/	/	/	Does not bioaccumulate.	/	/

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

The substance is not considered persistent, bioaccumulative and toxic (PBT).

12.6 Endocrine disrupting properties

No information.

12.7 Other adverse effects

No information.

12.8 Additional information

For product

Not classified as hazardous to the aquatic environment. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems. Dispose of in accordance with applicable waste disposal regulation.

Waste codes / waste designations according to LoW

No information.

Packaging

Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Deliver completely emptied containers to approved waste disposal authorities. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Uncleaned containers should not be perforated, cut or welded. Dispose of in accordance with applicable waste disposal regulation.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.

Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number or II	O number		
UN 1090	UN 1090	UN 1090	UN 1090
14.2 UN proper shipp	oing name		
ACETONE	ACETONE	ACETONE	ACETONE
14.3 Transport hazar	d class(es)		
3	3	3	3
3	3	3	3
14.4 Packing group			
II	П	П	II
14.5 Environmental h	nazards		
NO	NO	NO	NO
14.6 Special precauti	ons for user		
Limited quantities 1 L Packing Instructions P001, IBC02, R001 Transport category 2 Tunnel restriction code (D/E)	Limited quantities 1 L EmS F-E, S-D Flash point -16.99 °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y341 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 1 L Packing Instructions (Pkg Inst) 353 Maximum Net Quantity/Package (Max Net Qty/Pkg) 5 L Cargo Aircraft Only, Packing Instructions (CAO, Pkg Inst) 364 Cargo Aircraft Only, Maximum Net Quantity/Package (CAO, Max Net Qty/Pkg) 60 L Excepted quantities E2 ERG code 3H	Limited quantities 1 L
14.7 Maritime transp	ort in bulk according to IMO instruments		
	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)
 - Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline) not applicable

Regulation EC 648/2004 on detergents

No information.

Special instructions

No information.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: OTHER INFORMATION

Indication of changes

No information.

Key literature references and sources for data

Safety Data Sheet, Cure It Acetone, G& B Northwest Ltd, Revision Date: 6th December 2018, Version: 2.2.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW – see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC50 - Lethal Concentration to 50 % of a test population

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



- ✓ Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the
- ☑ Provided adequate transport data

BFNS

© Consulting

www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.