

# SA Primer

SA Primer is a solvent based, low viscosity polymeric priming solution.

## INTENDED USE

SA Primer is designed to improve the bond adhesion of self-adhesive and heat-activated bituminous membranes to a variety of substrates.

Products should be installed in accordance with the manufacturer's installation guidelines.

## STORAGE

SA Primer is supplied in 5 and 25 litre containers. Product must be stored under cover on a flat, level, and clean surface away from sources of ignition, including pilot lights and sparks. Keep containers tightly closed when not in use. In original unopened containers the shelf life is 12 months.

## INSTALLATION SUMMARY

Apply SA Primer by brush or roller at the recommended coverage rate (depending on the type and absorbency of the substrate). Apply a thin and even coat, and avoid pooling. Primer to be dry to touch prior to application of the self-adhesive membrane.

SA Primer should not be applied to wet surfaces. Apply the self-adhesive and heat-activated membrane as soon as possible after the primer is dry.

Ensure the substrate is structurally sound, free of surface laitance, oils, grease, dirt, moss, lichen, and loose material. The surface should be smooth and free from sharp projections and loose debris, and any material which would hinder adhesion.

For further details please consult our Flat Roofing Product Installation Guidelines or contact our technical services team.

## PRODUCT DATA

<b>Colour</b>	Black / Brown
<b>Coverage Rate <sup>(1)</sup></b>	4 – 8 m <sup>2</sup> per litre
<b>Application Rate <sup>(1)</sup></b>	0.12 – 0.25 Litres per m <sup>2</sup>
<b>Application Limits <sup>(2)</sup></b>	+4°C to +25°C
<b>Drying time <sup>(3)</sup></b>	5-30 mins
<b>Container Size</b>	5L & 25L

- (1) Depending on substrate porosity  
(2) Surfaces must be free of ice and water  
(3) Depending on ambient temperature

## PACKAGING

Description	Container Size	Product Code
SA Primer (5L)	5L	<b>20000724</b>
SA Primer (25L)	25L	<b>20000725</b>

## SAFETY, QUALITY & ENVIRONMENT

BMI Icopal products are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.



ISO 9001:2015  
44 100 21410102



ISO 14001:2015  
44 100 21410102

## TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

**T:** +44 (0) 330 123 4585

**E:** [technical.uk@bmigroup.com](mailto:technical.uk@bmigroup.com)



### BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW  
[bmigroup.com/uk](http://bmigroup.com/uk)

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact our BMI Icopal technical services team.