

DECLARATION OF PERFORMANCE

CE Marking - Declaration of Performance Cwt-y-Bugail Celtic Grade Roofing Slate



Welsh Slate roofing products conform to the requirements of the CE mark. The following table provides the necessary information required to demonstrate conformity of Cwt-y-Bugail Celtic Grade Roofing Slate

Intended to be used as discontinuous roofing and external cladding Dimensional variation Nominal thickness Individual thickness Deviation of length and width Deviation of edge straightness Deviation of rectangularity	9 mm 9 mm (< +/- 35%) Complies Complies Complies
Cwt-y-Bugail Celtic Intended to be used as discontinuous roofing and external cladding Dimensional variation Nominal thickness Individual thickness Deviation of length and width Deviation of edge straightness Deviation of rectangularity Mechanical resistance (Characteristic modulus of rupture)	9 mm (< +/- 35%) Complies Complies
Dimensional variation Nominal thickness Individual thickness Deviation of length and width Deviation of edge straightness Deviation of rectangularity	9 mm (< +/- 35%) Complies Complies
Nominal thickness Individual thickness Deviation of length and width Deviation of edge straightness Deviation of rectangularity	9 mm (< +/- 35%) Complies Complies
Individual thickness Deviation of length and width Deviation of edge straightness Deviation of rectangularity	9 mm (< +/- 35%) Complies Complies
Deviation of length and width Deviation of edge straightness Deviation of rectangularity	Complies Complies
Deviation of edge straightness Deviation of rectangularity	Complies
Deviation of rectangularity	
	Complies
Mechanical resistance (Characteristic modulus of rupture)	
Transverse	71.3 N/mm²
Longitudinal	36.5 N/mm²
Water permeability - water absorption	A1 (≤ 0.6%)
Apparent calcium carbonate content	≤ 5%
Durability	
Water absorption	A1 (≤0.6%)
Freeze-thaw cycling	Not required
Thermal cycling	т1
Sulphur dioxide exposure	S1
Non-carbonate carbon content	Complies: ≤ 2%
Release of dangerous substances: None in conditions of use as roofing	or external cladding
External fire performance: Deemed to satisfy	