

DECLARATION OF PERFORMANCE**DOP – BDPM WH/T**

- 1 Identification Code: **BDPM WH/T**: Bond It Pro-Mate Glazing Silicone
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior 12.5E. **G 20LM** Glazing Sealant
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0074
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤30%	Tested on aluminium with primer
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Kayleigh Cox-Nowak
Technical Manager
Elland

Issue 2: 3rd May 2019

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com

DECLARATION OF PERFORMANCE**DOP – BDPM WH/T**

- 1 Identification Code: **BDPM WH/T**: Bond It Pro-Mate Glazing Silicone
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior 12.5E. **G 20LM** Glazing Sealant
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0074
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤30%	Tested on aluminium with primer
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Kayleigh Cox-Nowak
Technical Manager
Elland

Issue 2: 3rd May 2019

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com