

Data Sheet Natural Slate

STONE	ELTERWATER	BROUGHTON	BURSTING	KIRKSTONE SEA GREEN	KIRKSTONE SILVER GREEN	BRANDY	BRANDY CRAG SILVER	KIRKBY	BRATHAY	BAYCUFF LORD	BAYCUFF
APPLICATIONS	90		Å (5		. e					200	A.)
Flooring - tiles	~	~	~	~	~	~	~	~	V	~	~
Flooring - slabs	~	~	~	~	~	~	~	~	~	~	~
Treads	~	~	~	V	V	V	V	V	V	V	V
External Cladding	V	~	~	~	V	~		~			72
Internal Lining	~	~	~	~	~	~	~	~			
Paving	~	V	V	V	V	V		V	V		V
Steps	~	~	~	~	~	~		V	V		~
Copings	~	~	~	~	~	~		~	V	~	~
Cills	~	~	~	V	V	V		V	V	V	V
Lintols	~	~	~	~	~	~		~			
Water Features	V	~	~	V	V	V		V	V		
Vanities	~	~	V	V	V	V	V	V	V		7
Reception Desk	~	~	~	~	V	V	V	~	V	V	V
FINISHES											
Honed	~	~	~	~	~	~	~	~	~	~	~
Polished										~	~
Waterjet		~	~			~	~				
Flamed	V	~	V	V	V	~	~	~	V		v
Sanded	V	~	V	V	V	V	V	V	V	V	V
Gritblasted	~	~	~	V	V	V	V	V	V	V	V
Line Textured	~	~	~	~	~	~		~	~		
Spot Textured	V	~	V	~	~	~		~	~		
Riven		~	- 72	12		- 22	V	~	~		68

All natural stone is subject to variation in colour, shading and natural markings, and natural weathering and oxidisation may occur. The finishes indicated are available on flat, face surfaces. For information on the possible finishes to edges or bespoke shaped details, please contact Burlington's technical team. In some applications it may be appropriate to seal natural stone. Acidic or chemical substances if left to dwell will damage natural stone and project specific cleaning and maintenance recommendations should be followed. Slip resistance performance for any stone should be assessed for suitability of its application. Lintols cannot be used as load bearing structural members.

For further information, please contact our technical sales/ customer service department.

October 2019

Burlington Stone

Cavendish House, Kirkby-in-Furness, Cumbria, LA17 7UN, England. Telephone: 01229 889661. Email: Sales@burlingtonstone.co.uk