

SAFETY DATA SHEET ACCORDING TO REGULATION (EC) 1907/2006**Product name: Cure It Topcoat****Creation date: 17.07.2019, Revision: 02.03.2023, version: 16.1****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name

Cure It Topcoat

UFI:

E500-W01J-R003-QVMC

<https://my.chemius.net/p/1GoCbR/en/pd/e4>**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses

Topcoat for roofing. Contact the manufacturer for any other applications.

Uses advised against

No information.

1.3 Details of the supplier of the safety data sheet

Manufacturer

G&B Northwest Ltd

Giants Hall Farm

WN6 8RY Wigan, United Kingdom

+44 (0)1942 518150

enquiries@gandbnw.co.uk

1.4 Emergency Telephone Number

Emergency

112

Manufacturer

+44 (0)1942 518150 Mon-Friday 8.30am – 4.30pm

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H335 May cause respiratory irritation.

Repr. 2; H361d Suspected of damaging the unborn child.

STOT RE 1; H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: DANGER**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains phthalic anhydride, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Contains:

Styrene

2.3 Other hazards**PBT/vPvB**

No information.

Endocrine disrupting properties

No information.

Additional information

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

For mixtures see 3.2.

3.2 Mixtures

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
Styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	cca. 33	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Repr. 2; H361d STOT RE 1; H372 Aquatic Chronic 3; H412	/	/
titanium dioxide	13463-67-7 236-675-5 - 01-2119489379-17	cca. 11	/	/	/

talc	14807-96-6 238-877-9 -	cca. 10	/	/	/
amorphous silica	112945-52-5 601-216-3 -	cca. 3	/	/	/
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	< 10	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373 Aquatic Chronic 3; H412	/	C
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1 265-185-4 - 01-2119490979-12	< 1	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 STOT RE 1; H372 Aquatic Chronic 2; H411	/	/
phthalic anhydride	85-44-9 201-607-5 607-009-00-4 01-2119457017-41	< 1	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Resp. Sens. 1; H334 STOT SE 3; H335	/	/
Cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6 - 01-2119524678-29	< 0,25	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Sens. 1; H317 Resp. Sens. 1; H334 STOT SE 3; H336	/	/

Notes for substances

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
---	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. No action shall be taken involving any personal risk or without suitable training. When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Use personal protective equipment. See section 8 for more information.

Following inhalation

Remove patient to fresh air - move out of dangerous area. In case of unconsciousness bring patient into stable side position and seek medical attention. Seek medical help immediately. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Keep at rest in a position comfortable for breathing.

Following skin contact

Wash affected skin areas thoroughly with plenty of water and soap. Take off all contaminated clothing. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Can cause irritation of respiratory system. Coughing, sneezing, nasal discharge, labored breathing. May cause allergic respiratory reaction. Long-term inhalation may cause severe damage to the health.

Following skin contact

Irritating to the skin. Itching, redness, pain. May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

Following eye contact

Causes severe eye irritation. Redness, tearing, pain.

Following ingestion

May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Alcohol-resistant foam.

Foam.

Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet. Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. Vapours and air can form explosive mixtures.

The vapor/gas is heavier than air and will spread along the ground. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂).

5.3 Advice for firefighters

Protective actions

Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel**Protective equipment**

Use personal protective equipment (Section 8).

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Take precautionary measures against static discharges.

Emergency procedures

Prevent access to unprotected personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

During intervention, use personal protective equipment (Section 8).

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

6.3 Methods and material for containment and cleaning up**For containment**

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Clean contaminated area with plenty of water. Use spark-proof tools. Ventilate the premises. Use only explosion-proof instruments and equipment. Prevent release into the sewer, water, basements or confined areas.

OTHER INFORMATION

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling****Protective measures****Measures to prevent fire**

Ensure adequate ventilation. Take precautionary measures against static discharges. Keep away from sources of ignition - no smoking. Use spark-proof tools. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air. In order to avoid the risk of fires and explosions, never use compressed air when handling. Empty containers may contain flammable product residues. Do not weld, solder, drill, cut.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Do not eat, drink or smoke while working. Do not breathe vapours/mist. Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8. In case of insufficient ventilation, wear suitable respiratory protection equipment.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition - no smoking. Keep in a cool, dry and well ventilated place. Store below 30°C. Keep away from strong oxidising agents. Keep away from peroxides. Keep away from reducing agents.

Packaging materials

Store only in original container. Metallic GRP containers.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)**Recommendations**

See identified uses in Section 1.2.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Occupational Exposure limit values**

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Styrene	215	50	425	100	India; source: Ministry of Labour and Employment, Permissible Levels of Certain Chemical substances in work environment	/
titanium dioxide	10	/	/	/	TWA 8h (inhalable fraction); EH40/2005 (UK)	/
titanium dioxide	4	/	/	/	TWA 8h (respiratory fraction); EH40/2005 (UK)	/
xylene	435	100	655	150	India; source: Ministry of Labour and Employment, Permissible Levels of Certain Chemical substances in work environment	/
Styrene (100-42-5)	430	100	1080	250	/	/
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
Phthalic anhydride (85-44-9)	4	/	12	/	Sen	/
Talc, respirable dust (14807-96-6)	1	/	/	/	/	/

Titanium dioxide respirable (13463-67-7)	4	/	/	/	/	/
Titanium dioxide total inhalable (13463-67-7)	10	/	/	/	/	/

Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
Styrene	Worker	inhalation	long term systemic effects	/	85 mg/m ³
Styrene	Worker	inhalation	short term systemic effects	/	289 mg/m ³
Styrene	Worker	inhalation	short term local effects	/	306 mg/m ³
Styrene	Worker	dermal	long term systemic effects	/	406 mg/kg bw/day
Styrene	Consumer	inhalation	long term systemic effects	/	10.2 mg/m ³
Styrene	Consumer	inhalation	short term systemic effects	/	174.25 mg/m ³
Styrene	Consumer	inhalation	short term local effects	/	182.75 mg/m ³
Styrene	Consumer	dermal	long term systemic effects	/	343 mg/kg bw/day
Styrene	Consumer	oral	long term systemic effects	/	2.1 mg/kg bw/day
titanium dioxide	Worker	inhalation	long term local effects	/	10 mg/m ³
titanium dioxide	Consumer	oral	long term systemic effects	/	700 mg/kg bw/day
amorphous silica	Worker	inhalation	long term systemic effects	/	4 mg/m ³
xylene	Worker	inhalation	long term systemic effects	/	77 mg/m ³
xylene	Worker	inhalation	short term systemic effects	/	289 mg/m ³
xylene	Worker	inhalation	short term local effects	/	289 mg/m ³
xylene	Worker	dermal	long term systemic effects	/	180 mg/kg bw/day
xylene	Consumer	inhalation	long term systemic effects	/	14.8 mg/m ³
xylene	Consumer	inhalation	short term systemic effects	/	174 mg/m ³
xylene	Consumer	inhalation	short term local effects	/	174 mg/m ³
xylene	Consumer	dermal	long term systemic effects	/	108 mg/kg bw/day
xylene	Consumer	oral	long term systemic effects	/	1.6 mg/kg bw/day
naphtha (petroleum), hydrodesulphurized heavy	Worker	inhalation	long term systemic effects	/	330 mg/m ³
naphtha (petroleum), hydrodesulphurized heavy	Worker	dermal	long term systemic effects	/	44 mg/kg bw/day

naphtha (petroleum), hydrodesulphurized heavy	Consumer	inhalation	long term systemic effects	/	71 mg/m ³
naphtha (petroleum), hydrodesulphurized heavy	Consumer	dermal	long term systemic effects	/	26 mg/kg bw/day
naphtha (petroleum), hydrodesulphurized heavy	Consumer	oral	long term systemic effects	/	26 mg/kg bw/day
phthalic anhydride	Consumer	oral	long term systemic effects	/	5 mg/kg bw/day
phthalic anhydride	Worker	oral	long term systemic effects	/	10 mg/kg bw/day
phthalic anhydride	Consumer	dermal	long term systemic effects	/	5 mg/kg bw/day
phthalic anhydride	Worker	dermal	long term systemic effects	/	10 mg/kg bw/day
phthalic anhydride	Consumer	inhalation	long term systemic effects	/	8.6 mg/m ³
phthalic anhydride	Worker	inhalation	long term systemic effects	/	32.2 mg/m ³
Cobalt bis(2-ethylhexanoate)	Worker	inhalation	long term local effects	/	235.1 µg/m ³
Cobalt bis(2-ethylhexanoate)	Consumer	inhalation	long term local effects	/	37 µg/m ³
Cobalt bis(2-ethylhexanoate)	Consumer	oral	long term systemic effects	/	55.8 µg/kg

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
Styrene	fresh water	/	0.028 mg/L
Styrene	marine water	/	0.0028 mg/L
Styrene	water treatment plant	microorganisms	5 mg/L
Styrene	fresh water sediment	dry weight	0.614 mg/kg
Styrene	marine water sediment	dry weight	0.0614 mg/kg
Styrene	soil	dry weight	0.2 mg/kg
Styrene	water, intermittent release	fresh water	0.04 mg/L
titanium dioxide	fresh water	/	0.127 mg/L
titanium dioxide	marine water	/	1 mg/L
titanium dioxide	water, intermittent release	/	0.61 mg/L
titanium dioxide	fresh water sediment	/	1000 mg / kg sediment dw
titanium dioxide	marine water sediment	/	100 mg / kg sediment dw
titanium dioxide	soil	/	100 mg/kg soil dw
amorphous silica	food chain	oral	60000 mg/kg
xylene	fresh water	/	0.327 mg/L
xylene	soil	dry weight	2.31 mg/kg
xylene	water, intermittent release	fresh water	0.327 mg/L
xylene	marine water	/	0.327 mg/L
xylene	water treatment plant	/	6.58 mg/L
xylene	fresh water sediment	dry weight	12.46 mg/kg
xylene	marine water sediment	dry weight	12.46 mg/kg
naphtha (petroleum), hydrodesulphurized heavy	soil	dry weight	0.4 mg/kg
phthalic anhydride	soil	/	0.173 mg/kg

phthalic anhydride	water treatment plant	/	10 mg/L
phthalic anhydride	fresh water sediment	/	3.8 mg/kg
phthalic anhydride	marine water sediment	/	0.38 mg/kg dwt
phthalic anhydride	marine water	/	0.1 mg/L
phthalic anhydride	fresh water	/	1 mg/L
phthalic anhydride	water, intermittent release	/	5.6 mg/L
Cobalt bis(2-ethylhexanoate)	fresh water	/	0.6 µg Co/L
Cobalt bis(2-ethylhexanoate)	marine water	/	2.36 µg Co/L
Cobalt bis(2-ethylhexanoate)	fresh water sediment	/	9.5 mg Co/kg
Cobalt bis(2-ethylhexanoate)	marine water sediment	/	9.5 mg Co/kg
Cobalt bis(2-ethylhexanoate)	soil	/	10.9 mg Co/kg
Cobalt bis(2-ethylhexanoate)	water treatment plant	/	0.37 µg Co/L

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Do not breathe vapours/aerosols. Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs. The use of adequate technical equipment must always take priority over personal protective equipment.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166). Do not use contact lenses.

Hand protection

Protective gloves (EN 374). The penetration time is determined by the protective glove manufacturer and must be observed. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Neoprene	/	/	EN 374
Nitrile	/	/	EN 374
Viton (fluorinated rubber)	/	/	EN 374
PVA	/	/	EN 374

Skin protection

At high risk of skin exposure chemical suits (EN ISO 6530:2005) and boots may be required (EN ISO 20345:2012). Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). Clothing for protection against chemical risks, with antistatic and fireproof properties.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties****Physical state**

liquid

Colour

grey

Odour

styren like

Important health, safety and environmental information

Odour threshold	No information.
Melting point/Freezing point	No information.
Boiling point or initial boiling point and boiling range	No information.
Flammability	No information.
Lower and upper explosion limit	No information.
Flash point	31 °C
Auto-ignition temperature	490 °C
Decomposition temperature	No information.
pH	No information.
Viscosity	kinematic: 9091 — 27273 at 20 °C Dynamic: 10000 — 30000 mPas at 20 °C
Solubility	Water: Insoluble Organic solvent: Partially soluble
Partition coefficient	No information.
Vapour pressure	6 hPa at 20 °C
Density and/or relative density	Density: 1.1 — 1.4 g/cm ³ at 20 °C
Relative vapour density	3.6
Particle characteristics	No information.

9.2 OTHER INFORMATION**Explosive properties**

No information.

Other information

Flammability Limits in Air: Upper 6.1 – 6.8%; Lower 0.9 – 1.1%. Soluble in most organic solvents.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Temperature above flashpoint: higher fire/explosion hazard.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures. The risk of polymerization.

10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. Extremes of temperature and direct sunlight. Take precautionary measures against static discharges.

10.5 Incompatible materials

Strong oxidising agents.
Peroxide. Reducing agents.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****(a) Acute toxicity**

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
Styrene	oral	LD ₅₀	rat	/	5000 mg/kg	/	/
Styrene	dermal	LD ₅₀	rat	24 h	> 2000 mg/kg bw	OECD 402	/
Styrene	inhalation	LC ₅₀	rat	4 h	11.8 mg/l	/	/
titanium dioxide	oral	LD ₅₀	rat	/	> 5000 mg/kg	OECD 425	/
titanium dioxide	dermal	LD ₅₀	rabbit	/	> 10000 mg/kg	/	/
titanium dioxide	inhalation	LC ₅₀	rat	4 h	> 6.82 mg/l	/	/
amorphous silica	dermal	LD ₅₀	rabbit	/	> 5000 mg/kg	/	/
amorphous silica	inhalation	LC ₅₀	rat	4 h	> 0.14 mg/l	OECD 403 OECD 403	/
xylene	oral	LD ₅₀	rat	/	> 4000 mg/kg bw	EU B.1 EU B.1	/
xylene	dermal	LD ₅₀	rabbit	/	> 5000 mg/kg bw	/	/
xylene	inhalation	LC ₅₀	rat	4 h	29091 mg/m ³	EU B.2 EU B.2	/
phthalic anhydride	oral	LD ₅₀	rat	/	1530 mg/kg bw	/	/
phthalic anhydride	dermal	LD ₅₀	rabbit	/	> 3160 mg/kg bw	/	/
phthalic anhydride	inhalation	LC ₅₀	rat	4 h	> 2.14 mg/l	/	/
Cobalt bis(2-ethylhexanoate)	oral	LD ₅₀	rat	/	3129 mg/kg	OECD 425	/

(b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
Styrene	rabbit	/	Irritating.	/	/

titanium dioxide	rabbit	/	Non-irritant.	OECD 404	/
amorphous silica	rabbit	/	Non-irritant.	OECD 404	/
xylene	rabbit	/	Mild irritating.	EU B.4	/
phthalic anhydride	rabbit	/	Irritating.	OECD 404	/
Cobalt bis(2-ethylhexanoate)	/	/	Non corrosive.	OECD 431	/

Additional information

Causes skin irritation.

(c) Serious eye damage/irritation**For components**

Name	Exposure route	Species	Time	result	Method	Remark
Styrene	/	rabbit	/	Irritating.	/	/
titanium dioxide	/	rabbit	/	No irritant effect.	OECD 405	/
amorphous silica	/	rabbit	/	No irritant effect.	OECD 405	/
xylene	/	rabbit	/	Mild irritating.	/	/
phthalic anhydride	/	rabbit	/	Irritating to eyes.	Draize test	/
Cobalt bis(2-ethylhexanoate)	/	/	/	moderately irritating	OECD 437, EU B.47	/
Cobalt bis(2-ethylhexanoate)	/	rabbit	/	Irritating.	OECD 405	/

Additional information

Causes serious eye damage.

(d) Respiratory or skin sensitisation**For components**

Name	Exposure route	Species	Time	result	Method	Remark
Styrene	-	/	/	Non sensitising.	/	/
titanium dioxide	dermal	mouse (female)	/	Non sensitising.	OECD 429	experimental value
titanium dioxide	dermal	guinea pig	/	Non sensitising.	OECD 406	/
amorphous silica	dermal	/	/	Non sensitising.	/	/
amorphous silica	inhalation	/	/	Non sensitising.	/	/
xylene	dermal	mouse	/	Non sensitising.	OECD 429	experimental value
phthalic anhydride	dermal	guinea pig	/	Sensitizing.	OECD 406	/
phthalic anhydride	inhalation	guinea pig	/	Sensitizing.	/	/
Cobalt bis(2-ethylhexanoate)	dermal	/	/	May cause sensitisation by skin contact.	/	/

(e) (Germ cell) mutagenicity**For components**

Name	Type	Species	Time	result	Method	Remark
Styrene	in-vitro mutagenicity	Bacteria	/	Ambiguous.	OECD 471	S.typhimurium G46,TA1530, TA1535, TA100, TA98, TA1538, TA1537
Styrene	in-vitro mutagenicity	Cell: Mammalian-Animal	/	Equivocal	OECD 476	Hamster
Styrene	in-vitro mutagenicity	/	/	Positive.	OECD 473, 479	Chromosome aberration assay
Styrene	in-vivo mutagenicity	mouse	/	Negative.	OECD 474, 486	/
titanium dioxide	in-vitro mutagenicity	/	/	Negative.	OECD 471 (Bacterial Reverse Mutation Test)	Ames test
titanium dioxide	in-vitro mutagenicity	mouse	/	Negative.	OECD 476	experimental value
titanium dioxide	in-vitro mutagenicity	Chinese hamster ovary	/	Negative.	OECD 473	Chromosome aberration assay

titanium dioxide	in-vivo mutagenicity	mouse	/	Negative.	/	/
amorphous silica	in-vitro mutagenicity	/	/	Negative.	OECD 471 (Bacterial Reverse Mutation Test)	Ames test
amorphous silica	in-vitro mutagenicity	Cell: Mammalian-Animal	/	Negative.	OECD 476	/
amorphous silica	in-vitro mutagenicity	/	/	Negative.	OECD 473	Chromosome aberration assay
amorphous silica	in-vivo mutagenicity	rat	/	Negative.	/	/
xylene	in-vitro mutagenicity	Chinese hamster ovary	/	Negative.	EU Method B.10	Chromosome aberration assay
xylene	in-vitro mutagenicity	Cell: Mammalian-Animal	/	Negative.	EU B.19	Hamster
xylene	in-vivo mutagenicity	mouse	/	Negative.	OECD 478	/
phthalic anhydride	in-vitro mutagenicity	S.typhimurium TA 1535, TA 1537, TA 98, TA 100 and TA102; Escherichia coli WP2 uvrA	/	Negative.	OECD 471	/
phthalic anhydride	in-vitro mutagenicity	Cell: Mammalian-Animal	/	Negative.	OECD 476	Hamster
phthalic anhydride	in-vitro mutagenicity	hamster	/	Equivocal	OECD 473	Chromosome aberration assay
Cobalt bis(2-ethylhexanoate)	in-vivo mutagenicity	/	/	Negative.	OECD 474	/
Cobalt bis(2-ethylhexanoate)	in-vivo mutagenicity	/	/	Negative.	OECD 475	/

(f) Carcinogenicity

For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
Styrene	inhalation	NOAEC	rat	/	≥ 4.34 mg/m ³ air	negative	OECD 453	/
Styrene	inhalation (vapours)	LOAEC	mouse (male/female)	/	0.09 - 0.18 mg/l	Positive	OECD 453	/
Styrene	oral	NOAEL	rat	/	≥ 2000 mg/kg bw/day	positive	/	/
Styrene	oral	LOAEL	mouse	/	150 mg/kg bw/day	Positive	/	/
titanium dioxide	inhalation	NOAEC	rat	/	5 mg/m ³ air	negative	OECD 453	lung tumours
titanium dioxide	oral	NOEL	rat	/	> 50000 ppm	negative	/	/
amorphous silica	oral	NOAEL	rat	/	1800 - 3200 mg/kg bw/day	negative	OECD 453	/
xylene	oral	/	rats and mice	/	500 - 1000 mg/kg bw/day	negative	EU B.32	1 - 3 weeks
xylene	oral	NOAEC	rat	/	2171 mg/m ³	negative	EPA OPPTS 870.3800	/
phthalic anhydride	oral	NOAEL	rat	105 weeks	1000 mg/kg bw/day	negative	/	/
phthalic anhydride	oral	NOAEL	mouse (male)	72 weeks	3570 mg/kg bw/day	negative	/	/
phthalic anhydride	oral	NOAEL	mouse (female)	72 weeks	1785 mg/kg bw/day	negative	/	/

(g) Reproductive toxicity

For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
Styrene	Effects on fertility	NOAEL/LOAEL	rat	60 days	100 - 200 mg/kg bw/day	Positive.	/	Inhalation

Styrene	Effects on fertility	NOAEL/LOAEL	rat	60 days	200 - 400 mg/kg bw/day	Positive.	OECD 422	oral
Styrene	Reproductive toxicity	LOAEC (P, F1)	rat	/	2.13 mg/L	Negative.	two-generation study; OECD 416	Inhalation
Styrene	Reproductive toxicity	NOAEC (P, F1)	rat	/	0.64 mg/L	Negative.	two-generation study; OECD 416	Inhalation
Styrene	Reproductive toxicity	NOAEC (F2)	rat	/	0.21 mg/L	Negative.	two-generation study; OECD 416	Inhalation
Styrene	Reproductive toxicity	LOAEC (F2)	rat	70 days	0.64 mg/L	Negative.	two-generation study; OECD 416	Inhalation
Styrene	Maternal toxicity + developmental toxicity	NOAEC/LOAEC	rat	50 days	1.08 - 2.15 mg/L	Positive.	/	Inhalation
Styrene	Maternal toxicity	LOAEC	rat	/	1.28 mg/L	Positive.	OECD 414	6-15 days; inhalation
Styrene	Developmental toxicity	NOAEC	rat	/	≥ 2.56 mg/L	Negative.	OECD 414	6-15 days; inhalation
Styrene	Maternal toxicity + developmental toxicity	NOAEC	rabbit	/	2.56 mg/L	Negative.	OECD	6-18 days; inhalation
amorphous silica	Reproductive toxicity	NOAEL	rat	/	497 mg/kg bw/day	Negative.	OECD 415	oral
amorphous silica	Teratogenicity	NOAEL	rat	/	1350 mg/kg bw/day	Negative.	OECD 414	oral
amorphous silica	Maternal toxicity	NOAEL	rat	/	1350 mg/kg bw/day	Negative.	OECD 414	oral
xylene	Developmental toxicity	NOAEC	rat	/	2171 mg/m ³	Negative.	OECD 414	Inhalation
xylene	Teratogenicity	NOAEC	rat	/	8684 mg/m ³	Negative.	OECD 414	Inhalation
phthalic anhydride	Reproductive toxicity	NOAEL	mouse (male)	72 weeks	3570 mg/kg bw/day	Negative.	/	oral
phthalic anhydride	Reproductive toxicity	NOAEL	mouse (female)	72 weeks	1785 mg/kg bw/day	Negative.	/	oral
phthalic anhydride	Reproductive toxicity	NOAEL	rat (female)	105 weeks	1000 mg/kg bw/day	Negative.	/	oral
phthalic anhydride	Maternal toxicity	NOAEL	rat	/	1000 mg/kg bw/day	Positive.	/	oral
phthalic anhydride	Teratogenicity	NOAEL	rat	/	1700 mg/kg bw/day	Positive.	/	oral

Summary of evaluation of the CMR properties

Suspected of damaging the unborn child.

(h) STOT-single exposure

For components

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Remark
phthalic anhydride	inhalation	-	/	/	/	/	/	May cause respiratory irritation.	/	/

Additional information

May cause respiratory irritation.

(i) STOT-repeated exposure

For components

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Remark
------	----------------	------	---------	------	----------	-------	-------	--------	--------	--------

Styrene	-	-	/	/	/	ear	/	Causes damage to organs through prolonged or repeated exposure.	/	/
Styrene	inhalation	NOAEC	rat (male)	28 days	/	/	3.47 mg/L air	/	/	/
Styrene	inhalation	NOAEC	/	28 days	/	/	2.13 mg/L	/	/	ototoxicity
Styrene	inhalation	NOAEC	mouse	28 days	/	/	0.181 mg/L	/	OECD 412	/
Styrene	inhalation	NOAEC	rat	28 days	/	/	0.688 mg/L	/	OECD 412	/
Styrene	inhalation	NOAEC	rat	90 days	/	nose	0.85 mg/L	/	/	/
Styrene	inhalation	NOAEC	rat	90 days	/	overall	2.13 mg/L	/	/	/
Styrene	oral	NOAEL	rat	/	/	/	1000 mg/kg bw/day	/	/	/
Styrene	oral	LOAEL	rat	/	/	/	2000 mg/kg bw/day	/	/	/
Styrene	oral	NOAEL	mouse	/	/	/	150 mg/kg bw/day	/	/	/
Styrene	oral	LOAEL	mouse	/	/	/	300 mg/kg bw/day	/	/	/
Styrene	inhalation	LOAEC	rat	/	/	/	0.21 mg/L	/	OECD 453	/
titanium dioxide	oral	NOEL	rat	90 days	/	/	24000 mg/kg bw/day	/	/	/
titanium dioxide	inhalation	NOEC	rat	/	/	/	50 mg/m ³	/	OECD 413	/
titanium dioxide	inhalation	NOEC	rat	/	/	/	10 mg/m ³	/	/	/
amorphous silica	oral	NOAEL	rat	/	/	/	4000 - 4500 mg/kg/day	/	OECD 408	/
amorphous silica	inhalation	NOEC	rat	/	/	/	1.3 mg/m ³	/	/	/
amorphous silica	inhalation	NOEC	rat	90 days	/	/	< 1.3 mg/m ³	/	OECD 413	/
amorphous silica	dermal	NOAEL	rabbit	/	/	/	≥ 10000 mg/kg bw/day	/	/	/
xylene	oral	NOAEL	rat	/	/	/	250 mg/kg bw/day	/	/	/
xylene	inhalation	NOAEC	rat	/	/	/	≥ 3515 mg/m ³	/	/	/
phthalic anhydride	oral	NOAEL	rat	7 weeks	/	/	1250 mg/kg bw/day	/	/	/
phthalic anhydride	oral	LOAEL	rat	7 weeks	/	/	2500 mg/kg bw/day	/	/	/
phthalic anhydride	oral	NOAEL	rat	105 weeks	/	/	500 mg/kg bw/day	/	/	/
phthalic anhydride	oral	LOAEL	mouse (male/female)	72 weeks	/	/	1717 - 2340 mg/kg bw/day	/	/	/
Cobalt bis(2-ethylhexanoate)	-	NOEL	rat (female)	/	/	/	5 mg/kg bw/day	/	/	/
Cobalt bis(2-ethylhexanoate)	-	NOAEL	rat (male)	/	/	/	40 mg/kg bw/day	/	OECD 422	/

Additional information

Causes damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

Symptoms related to the physical, chemical and toxicological characteristics

No information.

Interactive effects

No information.

11.2 Information on other hazards

Endocrine disrupting properties

No information.

Other information

No information.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
Styrene	LC ₅₀	4.9 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050 EPA OTS 797.1050	/
Styrene	EC ₅₀	4.7 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	/
Styrene	NOEC	1.9 mg/L	/	crustacea	<i>Daphnia magna</i>	OECD 202	/
Styrene	LC ₅₀	4.02 mg/L	96 h	fish	<i>Pimephales promelas</i>	OECD 203	/
Styrene	-	500 mg/L	30 min	bacteria	Activated sludge	OECD 209	/
titanium dioxide	EC ₅₀	10000 mg/L	72 h	algae	<i>Skeletonema costatum</i>	ISO 10253 ISO 10253	/
titanium dioxide	LC ₅₀	2000 mg/L	48 h	crustacea	<i>Daphnia magna</i>	/	/
titanium dioxide	EC ₅₀	> 100 mg/L	96 h	fish	<i>Brachydanio rerio</i>	/	/
titanium dioxide	LC ₅₀	> 1000 mg/L	96 h	fish	<i>Fundulus heteroclitus</i>	/	/
titanium dioxide	LC0	> 1000 mg/L	48 h	fish	<i>Leuciscus idus</i>	OECD 203 OECD 203	/
titanium dioxide	EC ₅₀	> 1000 mg/L	3 h	microorganisms	/	/	/
titanium dioxide	NOEC	≥ 1000 mg/L	3 h	microorganisms	Activated sludge	OECD 209 OECD 209	/
titanium dioxide	NOEC	5600 mg/L	72 h	algae	<i>Skeletonema costatum</i>	ISO 10253 ISO 10253	/
titanium dioxide	NOEC	≥ 3 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202, OECD 209 OECD 202, OECD 209	/
talca	LC ₅₀	100 mg/L	96 h	fish	<i>Danio rerio</i>	/	/
amorphous silica	EC ₅₀	≥ 1000 mg/L	24 h	crustacea	<i>Daphnia magna</i>	OECD 202	/
amorphous silica	LC ₅₀	> 10000 mg/L	96 h	fish	<i>Brachydanio rerio</i>	OECD 203	/
xylene	EC ₅₀	2.2 mg/L	73 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD 201	/
xylene	EC ₅₀	> 3.4 mg/L	48 h	crustacea	/	/	/
xylene	NOEC	3.4 mg/L	48 h	crustacea	<i>Ceriodaphnia dubia</i>	US EPA 600/4-91-003 US EPA 600/4-91-003	/

xylene	LC ₅₀	2.6 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	/	/
xylene	LC ₅₀	8.4 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	OECD 203	/
xylene	EC ₅₀	96 mg/L	24 h	microorganisms	<i>Nitrosomonas sp.</i>	/	/
xylene	NOEC	157 mg/L	3 h	microorganisms	Activated sludge	OECD 209 OECD 209	/
xylene	NOEC	0.44 mg/L	73 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD 201	/
phthalic anhydride	NOEC	32 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD 201 OECD 201	/
phthalic anhydride	LC ₅₀	> 99 mg/L	96 h	fish	<i>Oryzias latipes</i>	OECD 203 OECD 203	/
phthalic anhydride	EC ₅₀	> 1000 mg/L	3 h	microorganisms	Activated sludge	ISO 8192 ISO 8192	/
phthalic anhydride	EC ₅₀	13 mg/L	16 h	microorganisms	<i>Pseudomonas putida</i>	ISO 10712 ISO 10712	/
phthalic anhydride	EC ₅₀	731 mg/L	/	Plants	<i>Lactuca sativa</i>	/	/
phthalic anhydride	EC ₅₀	68 mg/L	72 h	algae	/	/	/
phthalic anhydride	EC ₅₀	71 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	/
Cobalt bis(2-ethylhexanoate)	EC ₅₀	283.1 µg/l	72 h	algae	/	/	/
Cobalt bis(2-ethylhexanoate)	EC ₅₀	654.2 µg/l	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD 201	/

Chronic (long-term) toxicity For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
Styrene	NOEC	1.01 mg/l	21 days	crustacea	<i>Daphnia magna</i>	/	/
Styrene	LOEC	2.06 mg/l	21 days	crustacea	<i>Daphnia magna</i>	/	/
Styrene	EC50	1.88 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 203 OECD 203	/
Styrene	LC ₅₀	120 mg/kg soil dw	14 days	earthworms	<i>Eisenia fetida</i>	OECD 207	/
Styrene	LOEC	65 mg/kg soil dw	/	earthworms	<i>Eisenia fetida</i>	OECD 207	burrowing time and mean percent weight change
Styrene	LOEC	180 mg/kg soil dw	/	earthworms	<i>Eisenia fetida</i>	OECD 207	survival
Styrene	NOEC	34 mg/kg soil dw	/	earthworms	<i>Eisenia fetida</i>	OECD 207	mean percent weight change
xylene	NOEC	> 1.3 mg/l	56 days	fish	<i>Oncorhynchus mykiss</i>	/	/
phthalic anhydride	NOEC	16 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	/
phthalic anhydride	EC50	42 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211 OECD 211	/
phthalic anhydride	LC ₅₀	560 mg/l	7 days	fish	<i>Danio rerio</i>	OECD 210 OECD 210	/
phthalic anhydride	LOEC	32 mg/l	60 days	fish	/	/	/
phthalic anhydride	NOEC	10 mg/l	60 days	fish	/	OECD 210 OECD 210	/
Cobalt bis(2-ethylhexanoate)	NOEC/EC10	86.4 µg/L	7 days	crustacea	<i>Ceriodaphnia dubia</i>	/	mortality
Cobalt bis(2-ethylhexanoate)	NOEC/EC10	19.7 - 20.1 µg/L	7 days	crustacea	<i>Ceriodaphnia dubia</i>	/	reproduction

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
Styrene	biodegradability	87 %	20 days	readily biodegradable	Similar to OECD 301D	/
xylene	biodegradability	87.8 %	28 days	readily biodegradable	OECD 301F	/
phthalic anhydride	biodegradability	68 %	10 days	readily biodegradable	OECD 301 D	/
phthalic anhydride	biodegradability	74 %	30 days	readily biodegradable	OECD 301 D	/
Cobalt bis(2-ethylhexanoate)	biodegradability	60 %	10 days	readily biodegradable	OECD 301 D	/

12.3 Bioaccumulative potential

Partition coefficient

For components

Name	Media	value	Temperature °C	pH	Concentration	Method
Styrene	Log Pow	3	/	/	/	/
xylene	Log Pow	2.77 - 3.15	/	/	/	/
phthalic anhydride	Log Pow	1.6	/	/	/	/

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
Styrene	BCF	/	74	/	/	/	Calculated value
titanium dioxide	BCF	<i>Oncorhynchus mykiss</i>	20	14 days	/	/	/
xylene	BCF	<i>Oncorhynchus mykiss</i>	25.9	56 days	/	/	/
phthalic anhydride	BCF	/	3.16 - 3.4	/	/	/	Calculated value

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

For components

Name	Type	Criterion	value	Evaluation	Method	Remark
Styrene	Soil	/	352	/	/	Koc
Styrene	Soil	log KOC	2.55	/	/	/
xylene	Soil	log KOC	2.73	/	/	/
xylene	Soil	/	537	/	/	Koc
phthalic anhydride	Soil	/	31	/	/	Koc

12.5 Results of PBT and vPvB assessment

No evaluation.

12.6 Endocrine disrupting properties

No information.

12.7 Other adverse effects

No information.

12.8 Additional information

For product

Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment. Do not allow to reach ground water, water courses or sewage system.

For components

titanium dioxide

This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

amorphous silica

This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

xylene

This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

phthalic anhydride

This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems. Dispose of in accordance with applicable waste disposal regulation.

Waste codes / waste designations according to LoW

No information.

Packaging

Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.





Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number or ID number			
UN 1866	UN 1866	UN 1866	UN 1866
14.2 UN proper shipping name			
RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			
Limited quantities 5 L Packing Instructions P001, R001 Special packing provisions PP1 Transport category 3 Tunnel restriction code (E)	Limited quantities 5 L EmS F-E, S-E Flash point 31 °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Special provisions A3	Limited quantities 5 L
14.7 Maritime transport in bulk according to IMO instruments			
	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)
not applicable

Regulation EC 648/2004 on detergents
No information.

Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant

women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

No information.

Key literature references and sources for data

Safety Data Sheet, Cure It Topcoat, G& B Northwest Ltd, Revision Date: 6th December 2018, Version: 1.2.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development
 OEL - Occupational Exposure Limit
 OJ - Official Journal
 OR - Only Representative
 OSHA - European Agency for Safety and Health at work
 PBT - Persistent, Bioaccumulative and Toxic substance
 PEC - Predicted Effect Concentration
 PNEC(s) - Predicted No Effect Concentration(s)
 PPE - Personal Protection Equipment
 (Q)SAR - Qualitative Structure Activity Relationship
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 RIP - REACH Implementation Project
 RMM - Risk Management Measure
 SCBA - Self-Contained Breathing Apparatus
 SDS - Safety data sheet
 SIEF - Substance Information Exchange Forum
 SME - Small and Medium sized Enterprises
 STOT - Specific Target Organ Toxicity
 (STOT) RE - Repeated Exposure
 (STOT) SE - Single Exposure
 SVHC - Substances of Very High Concern
 UN - United Nations
 vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.



- ☑ Provided correct labelling of the product
- ☑ Compliance with the local legislation
- ☑ Provided correct classification of the product
- ☑ Provided adequate transport data

BENS
 © [Consulting](https://www.bens-consulting.com) | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user

to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.