



INDIVIDUAL SLATE AND TILE SOAKERS

20 YEAR GUARANTEE

The individual soakers range is compatible with a wide range of tiles and slates with both right and left hand options where required.



FEATURES AND BENEFITS

- Quick and simple to install
- Thermally stable
- UV and acid rain resistant
- Lead alternative
- Reduced theft risk
- Creates no harmful run off into water courses
- Dry fix products eliminate the mortar installation and maintenance issues

APPLICATION

A range of lead-free preformed soakers for roof abutment details covering interlocking flat tiles, single lap slate and plain tiles, and double lap plain tiles and slates.

They are supplied preformed to save time and effort on site, and are finished by the use of a lead or lead replacement flashing product.

MATERIAL

Polypropylene

PLEASE SEE
OVERLEAF
FOR
COMPATIBILITY

PRODUCT CODE AND DIMENSIONS

| | | | |
|---|---|---|--|
| GREY  | Interlocking Tiles HD MDS H: 75mm W: 185mm L: 430mm | BLACK  | Interlocking Slates HD RCS H: 105mm W: 155mm L: 280mm |
| GREY  | Interlocking Tiles HD RRS H: 75mm W: 180mm L: 430mm | BLACK  | Plain Tiles HD PCS H: 75mm W: 100mm L: 170mm |
| GREY  | Interlocking Tiles HD RTS H: 75mm W: 175mm L: 410mm | BLACK  | Slates HD SS500 H: 85mm W: 100mm L: 300mm |
| GREY  | Interlocking Tiles HD SRRS H: 75mm W: 180mm L: 430mm | BLACK  | Slates HD SS600 H: 85mm W: 100mm L: 380mm |
| BLACK  | Interlocking Plain Tiles HD DTS H: 105mm W: 145mm L: 240mm | | |

RELATED PRODUCTS

| | |
|--|--|
|  | Universal Abutment Cover Flashing A continuous GRP cover flashing in Anthracite, designed as an effective lead alternative for roof abutments, code: HD UACF |
|  | Fast Flash An environmentally friendly, lead-alternative flashing. Available in 3 colours of 5 metre rolls in 4 widths, codes: Fast Flash 140, 280, 370, 560 |
|  | Tile & Slate Breathable Roofing Underlays Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180 |

INDIVIDUAL SOAKER COMPATIBILITY

| FORTICRETE | |
|------------|-----|
| Gemini | DTS |
| Minislate | DTS |



| LAGAN | |
|-------|------|
| Elite | SRRS |
| Flat | MDS |



| MARLEY | |
|------------|------|
| Ashmore | DTS |
| Duo Modern | MDS |
| Edgemere | SRRS |
| Melbourn | RCS |
| Modern | MDS |

| QUINN | |
|---------------|-----|
| Devenish | RTS |
| Rathmore | RTS |
| Western Slate | MDS |



| REDLAND | |
|-------------------|-----|
| Cambrian | RCS |
| Duo Plain | DTS |
| Landmark Slate 10 | RTS |
| Mini Stonewold | MDS |
| Richmond | RRS |
| Richmond 10 | RTS |
| Saxon 10 | RTS |
| Stonewold Mkl | MDS |

| RUSSELL | |
|----------|--------|
| Bute | SRRS** |
| Galloway | RTS |
| Grampian | MDS |
| Highland | MDS |
| Lothian | RTS |
| Moray | RTS |
| Polden | RTS |



| SANDTOFT (WIENERBERGER) | |
|-------------------------|--------|
| Balmoral | SRRS |
| Britlock | RCS* |
| Calderdale Slate | MDS |
| Cassius | SRRS** |
| Dual Calderdale | MDS |
| Rivius | SRRS** |
| TLE | RTS |
| 20/20 | SRRS** |

| DOUBLE LAP PRODUCTS | |
|----------------------|-------|
| Plain Tiles (All) | PCS |
| Slates 500mm x 250mm | SS500 |
| Slates 600mm x 300mm | SS600 |

* Subject to minimum rafter pitch of 30° and minimum headlap of 95mm ** Longer than the tiles; the length maybe trimmed at the head if required