

UNIVERSAL DRY FIX RIDGE KIT



Dry fix ridge systems involve covering the roof batten with a breathable ridge roll. The ridge roll is made from a polypropylene hydrophobic mesh that allows the roof to breathe. A pumped butyl self-adhesive strip then allows for a secure adhesion to the tile or slate. One by one, the ridge tiles are then installed over the ventilation ridge roll to secure it in place and are laid across the apex of the roof using plastic unions, ratchet clips, screws and nails. The FIX-R Universal Dry Fix Ridge Kit provides the recommended 5000mm² /m ventilation, equivalent to 5mm continuous gap requirements at the ridge, for the roof void.

- x1 Ventilated Ridge Roll
- x10 Ridge Batten Brackets
- x13 Universal Ridge Unions
- x1 Fixing Kit (Containing x26 Outer Clips, x13 Centre Clips, x13 Screws, x45 Nails)

Extension Packs are also available

KIT CONTENTS

BENEFITS

- Universal Ridge Unions compatible with concrete ridge tiles, half round & angled ridge tiles and hips (a hip kit must be used in conjunction with the Dry Fix Standard Ridge Kit)
- Mechanically fixed, mortar free
- Vapour permeable
- Self-adhesive butyl strip provides a water tight seal and permanent bond
- Conforms to BS 8612: Dry Fixed Ridge, Hip & Verge Systems for Slating & Tiling

Material	Roof Pitch	Ventilation	Installation Temperature
RIDGE ROLL: Polypropylene hydrophobic mesh, corrugated aluminium and pumped butyl self-adhesive strip	Suitable for pitches of 15° to 45°	Provides 5mm of continuous Ridge ventilation	5°C to 35°C
BATTEN BRACKETS: Stainless Steel			
UNIONS: Film grade polypropylene			
RATCHET CLIPS: Glass filled Nylon			