

# Diminishing Reproduction Stone Slate



Natural Weathered

Country Weathered

Turned York

**Main Slates**

HEIGHT	12"	18"	24"
22"	✓	✓	✓
26"	✓	✓	✓
30"	✓	✓	✓



**Top Slates**

HEIGHT	12"	18"
12"	✓	✓



**Under Eaves**

HEIGHT	17"	20"
17"	✓	



## TECHNICAL DATA

Size of Slates See table

Minimum Pitch (127mm lap)

Moderate Exposure 20°

Severe Exposure 25°

Maximum Pitch 90°

Typical Laps (mm) 75, 100

Covering Capacity (Net Slates/m<sup>2</sup>)  
Various

Weight of Slating (Approx, kg/m<sup>2</sup>)

75mm Lap 75

100mm Lap 82

127mm Lap 89

Battens Required (Net lin.m/m<sup>2</sup>)

75mm Lap 3.5

100mm Lap 3.6

Batten Size Recommended (fixed to BS 5534)  
50 x 25mm for rafters/supports not exceeding 600mm centres

40mm Slate Pegs

Reinforced Nylon

Aluminium

(Diameter of peg holes drilled on site should not exceed maximum 8mm)

Tested to BS EN 492:2012

Reproduction slates should always be laid tightly against adjacent slates to minimise the force of uplift and slate rattle. For extreme exposed locations a 'Mechanical Fix Specification for Gables' can be provided on request.

This product is a "Proprietary Product" it is therefore outside the scope of BS 5534:2014 (Slating and tiling for pitched roofs and vertical cladding). Code of practice and installation should therefore be carried out in accordance with manufacturer's instructions.

## For more information on our products

Telephone: 01484 666400

Fax: 01484 662709

E-mail: [info@greysartstone.co.uk](mailto:info@greysartstone.co.uk)

Website: [www.greysroofing.co.uk](http://www.greysroofing.co.uk)

Greys Artstone Limited, Lees Mill, Lees Mill Lane, Linthwaite, Huddersfield HD7 5QE