


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **Polimar UV**
- **Article number:** 700060
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU19 Building and construction work
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Liquid waterproofing top coat for roofs.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 IKO Europe nv
 d'Herbouvillekaai 80
 B-2020 Antwerpen
 Belgium
 Tel.: +32 (0)3 248 30 00
 E-mail: sds.europe@iko.com
- **Further information obtainable from:**
 National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24; National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**
 United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111
 Ireland National Poisons Information Centre Tel: +353 1 8092566
 Emergency call only for healthcare professionals

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 3 H226 Flammable liquid and vapour.
 Acute Tox. 4 H332 Harmful if inhaled.
 Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 Skin Sens. 1 H317 May cause an allergic skin reaction.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

 GHS02 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
 sebacate derivatives
 benzotriazole derivatives
 aliphatic polyisocyanate
 trimethylhexane-1,6-diamine

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: Polimar UV

(Contd. of page 1)

Isophorone diisocyanate polymer

4,4'-isopropylidenediphenol

• Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• UFI : MNHM-D8YA-T006-8R0V
• Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

• 3.2 Chemical characterisation: Mixtures
• Description: Resin mixture

• Dangerous components:

CAS: 426822-87-9	aliphatic polyisocyanate Skin Sens. 1, H317	10-25%
CAS: 26444-49-5 EINECS: 247-693-8	diphenyl tolyl phosphate Aquatic Acute 1, H400 Aquatic Chronic 3, H412	≥10-<25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	10<20%
CAS: 140921-24-0 ELINCS: 411-700-4 Reg.nr.: 01-0000015906-63	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	≥5-<10%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24	Isophorone diisocyanate polymer Skin Sens. 1, H317; STOT SE 3, H335	≥5-<10%
CAS: 115-86-6 EINECS: 204-112-2 Reg.nr.: 01-2119457432-41	triphenyl phosphate Aquatic Acute 1, H400; Aquatic Chronic 2, H411	2.5-5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	≥1-<2.5%
CAS: 26488-60-8 EINECS: 247-735-5	2-Ethylexyl (6 -isocyanatohexyl)-carbamate Acute Tox. 3, H331 Resp. Sens. 1, H334 Skin Sens. 1B, H317; STOT SE 3, H335 Aquatic Chronic 3, H412	≥1-<2.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: Polimar UV

(Contd. of page 2)

CAS: 104810-48-2 ELINCS: 400-830-7	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -hydroxy- Aquatic Chronic 2, H411 Skin Sens. 1, H317	≥ 0.5 - $< 1\%$
CAS: 41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.3-0.4%
CAS: 82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.3-0.4%
CAS: 104810-47-1	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- Aquatic Chronic 2, H411 Skin Sens. 1, H317	0.3-0.4%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317 Aquatic Chronic 3, H412	0.2-0.3%
CAS: 80-05-7 EINECS: 201-245-8 Reg.nr.: 01-2119457856-23	4,4'-isopropylidenediphenol Repr. 1B, H360F Eye Dam. 1, H318 Skin Sens. 1, H317; STOT SE 3, H335	0.1-0.2%
CAS: 1185-81-5 EINECS: 214-688-7 Reg.nr.: 01-2119841260-50	dibutylbis(dodecyl)thiostannaan Muta. 2, H341; Repr. 1B, H360; STOT RE 1, H372 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	0.1%

SVHC

CAS: 80-05-7 4,4'-isopropylidenediphenol

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:

 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: **Polimar UV**

(Contd. of page 3)

- **5.2 Special hazards arising from the substance or mixture** Not applicable.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:	
--	--

CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
--	--

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

CAS: 115-86-6 triphenyl phosphate	
--	--

WEL	Short-term value: 6 mg/m ³
	Long-term value: 3 mg/m ³

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
Type A2/P2

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: Polimar UV

(Contd. of page 4)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• **Protection of hands:** Solvent resistant gloves

• **Material of gloves**

brief contact : PVC, neoprene rubber

prolonged contact : nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **Appearance:**

Form: Viscous

Colour: Various colours

• **Odour:** Characteristic

• **Odour threshold:** Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 160 °C

• **Flash point:** 44 °C

• **Flammability (solid, gas):** Not applicable.

• **Ignition temperature:** 315 °C

• **Decomposition temperature:** Not determined.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

• **Explosion limits:**

Lower: 1.5 Vol %

Upper: 10.8 Vol %

• **Oxidising properties** Not determined.

• **Vapour pressure at 20 °C:** 3.4 hPa

• **Density at 20 °C:** 1.17 g/cm³

• **Relative density** Not determined.

• **Vapour density** Not determined.

• **Evaporation rate** Not determined.

• **Solubility in / Miscibility with water:**

Insoluble.

• **organic solvents:** Miscible with many organic solvents.

• **Partition coefficient: n-octanol/water:** Not determined.

• **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: **Polimar UV**

(Contd. of page 5)

- **Solvent content:**
- Organic solvents: 15.1 %
- Solids content: 72.6 %
- **9.2 Other information** No further information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	>18.1 mg/l (rat)
------------	----------	------------------

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

CAS: 115-86-6 triphenyl phosphate

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (kon)

Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

CAS: 26488-60-8 2-Ethylexyl (6 -isocyanatohexyl)-carbamate

Oral	LD50	>2,500 mg/kg (rat)
Inhalative	LC50/4 h	0.521 mg/l (rat)

CAS: 25620-58-0 trimethylhexane-1,6-diamine

Oral	LD50	900 mg/kg (rat)
------	------	-----------------

CAS: 80-05-7 4,4'-isopropylidenediphenol

Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)

(Contd. on page 7)

Trade name: Polimar UV

(Contd. of page 6)

CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	1,500 mg/kg (rab)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Splashes in the eyes may cause irritation and reversible local damage.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

• **12.1 Toxicity**

• **Aquatic toxicity:**

CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Inhalative	LC50	193 mg/l (daphnia)
		316 mg/l (fish)

CAS: 115-86-6 triphenyl phosphate

Inhalative	LC50	0.4 mg/l (fish)
	EC50	1 mg/l (daphnia)

CAS: 26488-60-8 2-Ethylexyl (6 -isocyanatohexyl)-carbamate

Inhalative	LC50	>100 mg/l (fish) (96h)
	EC50	>100 mg/l (daphnia) (48h)

CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan

	EC50	0.11 mg/l (daphnia)
--	------	---------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018


Trade name: **Polimar UV**

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG | UN1866 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG | UN 1866, RESIN SOLUTION, 3, III, (D/E)
UN1866 HARS, OPLOSSING
UN 1866, Resin solution, 3, III, (44°C c.c.)
RESIN SOLUTION |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids.
3 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG | III |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: | Not applicable. |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Flammable liquids.
30
F-E, S-E |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: <hr style="border-top: 1px dashed red;"/> <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | |
| <ul style="list-style-type: none"> · Transport category · Tunnel restriction code | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
3
D/E |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1866 RESIN SOLUTION, 3 |

GB

(Contd. on page 9)

Trade name: **Polimar UV**

(Contd. of page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40

• **Regulation (EU) No 649/2012**

CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan

Annex I Part 1

• **National regulations:**• **Other regulations, limitations and prohibitive regulations**• **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 80-05-7 4,4'-isopropylidenediphenol

-
- 15.2 Chemical safety assessment:**
- A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

• **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360 May damage fertility or the unborn child.
- H360F May damage fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

• **Contact:** sds.europe@iko.com• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2018

Version number 4

Revision: 20.11.2018

Trade name: Polimar UV

(Contd. of page 9)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Muta. 2: Germ cell mutagenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• * **Data compared to the previous version altered.**

GB