

# DECLARATION OF PERFORMANCE

Document Reference N°: 01514013 150305

- 1 Unique identification code of the product type:  
**01514013**
- 2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):  
**IKO base Quadra T/F 7.5 m**
- 3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Flexible sheets for waterproofing - Reinforced bitumen sheets for roof waterproofing  
Bitumen water vapour control layers**
- 4 Name, registered trade name or registered trade mark and contact address of the manufacturer:  
**IKO nv d'Herbouvillekaai 80 B-2020 Antwerpen - Belgium  
tel. +32 3 248.30.00 - www.be.iko.com - www.ikodop.eu**
- 5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
-
- 6 System(s) of assessment and verification of constancy of performance of the product:  
**System 2+, except for vapor control layers system 3.**
- 7 In case of the declaration of performance concerning a construction product covered by a harmonized standard:  
**FPC certificate obtained from SGS Notified Body, registered under registration number 0958. Certificate number: 0958-CPR-2009/1.**
- 8 Declared performances:

Characteristic	Result	Units	Tolerance	Ref. Norm
External fire performance (Note 1)	Froof (t1, t2, t3, t4)			<b>EN 13707:2004 + A2:2009</b>
Reaction to fire	Euroclass E			
Watertightness	Pass			
Tensile force length	700	N/50 mm	± 20%	
Tensile force width	450	N/50 mm	± 20%	
Elongation length	30	%	± 15	
Elongation width	40	%	± 15	
Root resistant	NPD			
Resistance to static loading: method A	NPD	kg		
Resistance to impact: method A	NPD	mm		
Resistance to tearing length/width	NPD	N	-0/+200	
Peel resistance of joints initial: length/width	NPD	N/50 mm	-0/+200	
Shear resistance of joints: initial	NPD	N/50 mm	-0/+200	
Pliability initial (up/under)	≤-5	°C		
Durability: pliability after heat oven exposure	NPD	°C	-10/+0	
Durability: heat flow after heat oven exposure	100	°C	-0/+50	
Durability: UV heat and water	NPD	-		
Dangerous Substances (Note 2)				

NPD=No Performance Determined


Note 1: Since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone.

Note 2: In absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

- 9 The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

(place and date of issue): Antwerpen, 29/3/2022

Signed for and on behalf of the manufacturer by:



Dirk Theuns, CEO IKO n.v.  
(name and function)