

IKOpro BRIDGING TAPE

PRODUCT INFORMATION

IKOpro Bridging Tape is a self-adhesive de-bonding tape used where small amounts of movement may occur, and to bridge gaps in all panelled joints within **IKO Polimar** liquid waterproofing systems.

Size	Product Code
45m x 75mm	MW700206



DISCLAIMER

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.

USE

Used as a de-bonding tape at positions of expected minimal movement (less than 5mm) such as joints in timber panels, seams, small gaps or where differential movement no greater than 5mm is expected.

PERFORMANCE & COMPOSITION

Composition:	Aluminium Foil
Form:	Roll
Colour:	Aluminium

DIRECTIONS FOR USE

APPLICATION

IKOpro Bridging Tape should be used to bridge all small gaps (less than 5mm), joints, seams, etc. where minimal movement of less than 5mm is may occur. The bridging tape backing should be pressed firmly onto the substrate surface and care should be taken to ensure that the edges are firmly pressed down flush with the surface profile.