



Uni-Line® Slate Vent is a universal In-line Slate Vent that suits most man-made and natural slates.

Product features & benefits

- In-line design
- Fully wind tunnel tested
- Built in downpipe allows direct ventilation to roof space
- No soil/mechanical adaptor required

Area of application

Suitable for:

- 600 x 300mm (24" x 12") and 500mm x 250mm (20" x 10") fibre and natural double lap slates
- High or low level roof space ventilation
- For roof pitches of 22.5° and above
- Most natural and fibre cement slates
- Batten cutting only required below 225mm gauge (when used with 500mm x 250mm double-lap slates)

Material

UV resistant Polypropylene

Colours / Product Codes

Dark Slate KG9630-0403
Slate Grey KG9630-0429

Dimensions / Weight (per carton)

600mm long x 380mm wide x 141mm deep (including adaptor/downpipe) / 11.5kg

Packaging

10 pcs per carton

Related products

Uni-Flexipipe KG979900

Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.



Installation

The vent is positioned directly in-line with the slates below, and an inverted T opening is cut within the underlay to accommodate the downpipe. To ensure the integrity of the underlay a Klobber Underlay Seal is strongly recommended. Once the downpipe has been

located through the underlay opening, the slate vent is located on and fixed to the slate batten. The slates either side of the vent are laid and trimmed if necessary.

PERFORMANCE / TECHNICAL DATA

Provides 6,500mm² effective vent area.

| | | | |
|--------------------|---|-----------------------------|------------------------------|
| Vent spacing | 5mm opening at 1.2m centres 10mm opening at 0.6m centres | | |
| Airflow resistance | 15 litres/sec 24 Pascals | 30 litres/sec 96 Pascals | 60 litres/sec 384 Pascals |

TS-00#14-UK-0918. We assume no liability for typing errors.

Klobber Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klobber.co.uk · www.klobber.co.uk

