

# Declaration of Performance

## G4209LSCPR

1. Unique identification code of the product-type:  
Acoustic Roll
2. Intended use or uses:  
Thermal Insulation for Buildings (ThIB)
3. Manufacturer:  
Knauf Insulation Ltd.  
Pont-Y-Felin, Cwmbran, NP44 2YQ Torfaen - South Wales  
UK  
www.knaufinsulation.com - dop@knaufinsulation.com
4. Authorised representative:  
Knauf Insulation AB  
Gardatorget 1  
412 50 Goteborg  
Sweden
5. System or systems of assessment and verification of constancy of performance:  
AVCP System 1 for Reaction to Fire  
AVCP System 3 for the other characteristics
- 6a. Harmonized Standard:  
  
EN 13162:2012 + A1:2015  
  
Notified body or bodies:  
AVCP System 1: (Notified certification body) 0402 - RISE Research Institutes of Sweden AB - - -  
  
AVCP System 3: (Notified testing laboratory) 0402 - RISE Research Institutes of Sweden  
AB - - - - -
- 6b. European Assessment document: not applicable  
European Technical Assessment: not applicable  
Technical Assessment Body: not applicable  
Notified body/ies: not applicable
7. Declared Performances:  
See next page

Essential Characteristics	G4209LSCPR		Harmonised technical standard
	Performance {f}	Acoustic Roll	
Thermal Resistance	Thermal conductivity (W/mK)	NPD	EN 13162:2012 + A1:2015
	Thermal Resistance	See product label	
	Thickness range (mm)	25 - 100	
	Thickness tolerance	T1	
Reaction to Fire	Reaction to fire	A1	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD {a}	
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal Resistance	NPD{b}	
	Thermal conductivity	NPD	
	Durability characteristics	NPD {c}	
Compressive Strength	Compressive Stress / Compressive Strength	NPD	
	Point Load	NPD	
Tensile / Flexural strength	Tensile strength perpendicular faces	NPD {d}	
Durability of compressive Strength against ageing / degradation	Compressive creep	NPD	
Water Permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
Water vapour permeability	Water vapour transmission, water vapour diffusion resistance factor	NPD	
Impact noise transmissions index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Air flow resistivity	NPD	
Acoustic absorptions index	Sound absorption	NPD	
Direct airborne sound insulation index	Air flow resistivity	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD {e}	
Continuous glowing combustion	Continuous glowing combustion	NPD {e}	
NPD - No performance determined			

8. Appropriate Technical Documentation and / or Specific Technical Documentation:

Not applicable

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for an on behalf of the manufacturer by:

Mark Yeandle - Plant manager  
(Name and function)



Cwmbran - 15-12-20  
(Place and date of issue)

{a} No change in reaction to fire properties for MW Products. The fire performance of MW does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.

{b} Thermal conductivity of MW products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air

{c} For dimensional stability thickness only

{d} This characteristic also covers handling and installation

{e} European test methods are under development

{f} Also valid and applicable for multilayers