

Circular Saw LXT®

DSS611Z

18 V • 3 700 min⁻¹ • 165 mm



LXT 18V

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	3700 min ⁻¹
Max. Cutting Depth at 45°	40 mm
Max. Cutting Depth at 50°	36 mm
Max. Bevel Range (Left)	0 / 45 °
Blade Diameter	165 mm
Bore Size (Arbor Diameter)	15,88 / 20 / 25,4 / 30 mm
Tool weight with battery (EPTA)	2,9 - 3,2 kg
Product Dimensions (L x W x H):	347 x 202 x 228 mm
Plastic Carrying Case	✓
Blade Diametre	165 mm

User benefits

- Smooth cutting at high rotational speed of 3,700 RPM
- Easy to grip, ergonomically designed handle with soft grip provides a sure and comfortable grip
- Safety cover with calibration line for adjusting cutting depth
- Bevel cuts 0° - 45°
- Large bevel lock lever; Easy to operate even if the machine is placed close to the wall, because you do not need to reach for the rear of the machine to turn the lever
- Externally accessible brushes for easy serviceability

EAN 0088381663014

Link to product - www.makitauk.com



Related products

■ Standard AC

164095-8
Parallel Guide



783203-8
Hex Wrench 5 Mm



■ Other

User manual