

**FIX-R**  
**CLASSIC**  
**FLAT ROOFING**

Product data sheet

FIX-R Classic Fabric 10 | 001

# FABRIC 10

---

A non-woven, spun-bound, polypropylene reinforced fabric.

---

## Description

FIX-R Classic Fabric 10 is a non-woven, spun-bound, polypropylene reinforced fabric.

## Recommended For

For use when applying FIX-R Classic Liquid 10 over existing Built-Up Felt and Asphalt Roofs.

## Application Procedure

Fabric 10 is applied between two coats of FIX-R Classic Liquid 10. Can be used in the following conditions:

- Temperature Range: 5-35°C
- Relative Humidity: <85%

## Packaging and Shelf Life

Fabric 10 is supplied in white rolls 25m x 1m

## Storage

Fabric 10 must be kept in a cool and dry place, at temperatures of between 5-25°C.

- Made of 100% polypropylene material at high temperature and spun-bound
- Non-toxic, non-irritant
- Made from materials conforming to FDA Standard requirements
- No other chemical composition, stable, non-toxic, no smell, safe for sensitive skin

## Safety

Fabric 10 is a non-hazardous material.

## Technical specification

<b>Material</b>	100% Polypropylene
<b>Colour</b>	White
<b>Technology</b>	Spunbound

	<b>Units</b>	<b>FIX-R Classic Fabric 10</b>	
Weight	g/sq.m	50	
Colour		White	
Thickness	Mm	0.38	
Tensile Strength	n/5cm	MD	104
		CD	89
Elongation	%	MD	70
		CD	80

Certified quality, environmental and occupational health & safety management systems: ISO 9001/14001 & OHSAS 18001.