

Pacifyre® MK II Fire Sleeve (P)

for penetrations of plastic pipes (non-insulated) 15 - 204 mm

(U 04 05)




Features and Benefits

- for pipe penetrations in accordance with e.g. DIN 4102-11 or DIN EN 1366-3 in walls (solid walls or light partition walls) and ceilings with fire protection requirements
- the sleeve provides a guaranteed protection against fire, smoke and noise
- expansion and contraction of the pipe remains possible
- minimum space required, therefore can be applied in areas of hard accessibility
- a higher flexibility due to minimal overhang on wall and ceiling seals
- no tools, drilling or extra fixing materials needed
- simple and easy to install
- maintenance free
- noise reduction test report from IRB (Fraunhofer Institut - Germany) available
- tested according to EN 1366-3
- in accordance with many EU country building regulations
- European approval: ETA-20/0732



Part No.	D (mm)	DN	d (mm)	Pack 1	Pack 2
2151015017	15 - 17	15	40	1	12
2151018020	18 - 20	20	45	1	12
2154024026	23 - 28	25	50	1	12
2154030032	29 - 36	32	55	1	12
2154039041	38 - 44	40	65	1	12
2154048050	46 - 52	50	75	1	12
2154051053	48 - 55	52	75	1	12
2154054056	52 - 58	56	80	1	12
2154057059	55 - 61	58	85	1	12
2154063065	61 - 67	63	90	1	12
2154075077	70 - 79	75	100	1	6
2154078080	74 - 82	80	105	1	6
2154090092	86 - 94	90	115	1	6
2154108110	104 - 113	110	135	1	6
2158123125	120 - 128	125	160	5	-
2158135137	131 - 139	135	170	5	-
2158138140	136 - 144	140	175	5	-
2158159161	155 - 164	160	195	5	-
2158180182	175 - 184	180	215	5	-
2152198200	195 - 204	200	245	4	-

For Pacifyre® MK II Fire Sleeves in other sizes, please contact your Walraven Sales Company.



Complementary

Tangit FP 550 2C Fire Protection Foam
Tangit FP 800 Fire Protection Coating
Pacifyre® FPM

Complementary

Pacifyre® ID-Card