





# **GROVEBURY**

Quicker and easier to lay than single pantiles, Grovebury offers a wide range of granular and through-coloured options, from classic Slate Grey to Antique Red.

#### **KEY ADVANTAGES**

- Traditional pantile profile blends with a wide range of roofing styles
- Quick laying: saves time and money during installation
- Wide variety of colours and surface textures

## TECHNICAL DATA

Size (overall)	418 × 332mm
Minimum Pitch and Headlap	450 +400
Through coloured Granular	15° at 100mm headlap / 17.5° at 75mm headlap 22.5° at 100mm headlap / 30° at 75mm headlap
Maximum Pitch (subject to fixing s	pecification) 90°
Maximum Headlap	125mm
Minimum Gauge/Batten Spaci	ng 293mm
Maximum Gauge/Batten Spac	•
Through coloured Granular	17.5° at 318mm / 17.5° and over 343mm below 30° at 318mm / 30° and over 343mm
Hanging Length (approx.)	397mm
Cover (all figures are net and do not a Linear cover of 1 tile Covering capacity 10.5 t	allow for wastage) 300mm illes/m² at 318mm gauge / 9.7 tilles/m² at 343mm gauge
Weight 49kg/m² at 318mm gauge / 46kg/m² at 343mm gauge	
per pallet, including pallet (appro per 1000	1.07 tonnes 4.70 tonnes
Battens Required (at max. gauge)	2.92m/m <sup>2</sup>
Batten Size Rafter centres up to 450mm Rafter centres up to 600mm	38 × 25mm 50 × 25mm
Fixing Clips	Eaves, Verge & Tile Clips
Nail Size for Tiles#	70 × 3.75mm (A/A)
Pallet Quantities Tile	es per pallet 216 / Tiles per pack 36 / Packs per pallet 6
#(A/A) Aluminium Alloy	

## FITTINGS & ACCESSORIES

Verge	Cloaked Verge Ambi-Dry Verge Rapid Verge
Hip	Third Round Hip Dry Hip Rapid Hip
Valley	125 GRP Valley Dry Valley
Ridge	Half Round Ridge Half Round Monoridge
Ventilation Systems	RedVent EavesVent RedVent 25 Over-Fascia Vent Rapid Eaves Vent Top Edge Abutment Ventilation DryVent Ridge Continuous Ridge System Uni-Vent Rapid Ridge/Hip DryVent Monoridge RedLine Vent Tile Rapid Roof Vent 8.8k ThruVent Tile

#### **COLOURS**

