

According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Trade name: FIX-R Aluminium Paint

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available

- Application of the substance / the preparation: Aluminium Roof Paint
- Details of the supplier of the safety data sheet

FIX-R

Harding Way,

St Ives,

Cambridgeshire.

PE27 3YJ

Tel: 01480 466777 Fax: 01480 290133 Email: info@fix-r.co.uk www.fix-r.co.uk

SECTION 2: Hazards Identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R10-67: Flammable. Vapours may cause drowsiness and dizziness.

• Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHSO2 GHS07

- Signal word Warning
- Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local / regional / national /

international regulations.

SECTION 3: Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

EC number: 919-857-5	Koolwaterstoffen,C9-C11, n-alkanen, isoalkanen, cyclische, <2% aromaten Xn R65 R10-66-67 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
EC number: 919-446-0	Aluminiumpasta F R11 R66 Flam. Sol. 1, H228	10-25%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First Aid Measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further information available.

SECTION 5: Firefighting Measures

- Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture: Not applicable.
- Advice for fire fighters
- Protective equipment: No special measures required.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

SECTION 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course of sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections

See section 7 for information on safe handling.

See section 8 for information on personal protection equipment.

See section 13 for disposal information.

SECTION 7: Handling and Storage

- Handling:
- Precautions for safe handling: No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away Do not smoke.
 Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store at temperature between 0°C and 35°C.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

SECTION 8. Exposure Controls/Personal Protection

- Additional information about design of technical facilities: No further data; see item 7.
- Control parameters
- Ingredients with limit values that require monitoring at workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- Exposure controls
- Personal Protective Equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands: Solvent resistant gloves
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculate in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

Eye protection:



Tightly sealed goggles

SECTION 9: Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance:

Form: Viscous
 Colour: Silver grey
 Odour: Solvent-like
 pH-value: Not determined

Change in condition

Boiling point/Boiling range: 130°C
 Flash point: 36°C

o **Self-igniting:** Product is not self-igniting.

o **Danger of explosion:** Product is not explosive. However, formations of explosive

air/vapour mixtures are possible.

Explosion limits:

Lower
 Upper:
 Vapour pressure at 20°C:
 Density at 20°C:
 Solubility in / Miscibility with water:

Organic solvents: Miscible with many organic solvents.

Viscosity

o Kinematic at 20°C: 85 s (DIN 53211/4)

Solvent content:

o VOC (EC) VOC limit value (cat A/i) 500 g/L 2010.

Product contains 300 g/L.

SECTION 10: Stability and Reactivity

- Chemical stability
- Thermal decomposition / conditions to be avoided: Stable at environment temperature.
- Possibility of hazardous reactions: Forms flammable gases/fumes.
- Conditions to avoid: No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:
- Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

SECTION 11: Toxicological Information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values relevant for classification:
- Koolwaterstoffen, C9-C11, n-alkanen, isoalkanen, cyclishe, <2% aromaten
 - Oral: LD50 > 5000 mg/kg (rat)
 - Dermal: LD50 > 5000 mg/kg (rab)
 - o Inhalative: LC50/4 h >4951 mg/l (rat)
 - Primary irritant effect:
 - On the skin: Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
 - On the eye: Irritating effect.
 - Sensitization: No sensitizing effects known.

SECTION 12: Ecological Information

Toxicity

- Aquatic toxicity: No further relevant information available.
 - Persistence and degradability: No further relevant information available.
 - Behaviour in environmental systems:
 - Bio accumulative potential: No further relevant information available.
 - Mobility in soil: No further relevant information available.
 - Additional ecological information:
 - General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment.
- **PBT:** Not applicable.
- VPvB: Not applicable.
- Other adverse effects: No further relevant information available.

SECTION 13: Disposal Considerations

- Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

SECTION 14: Transport Information

 UN nur 	mber	
 ADR, IMDG 		1268
UN proper shipping name		
0	ADR	PETROLEUM PRODUCTS, N.O.S. (aliphatic white spirit)
0	IMDG	ÚN 1268, Petroleum products n.o.s., 3, III, (35°C c.c.)

Transport hazard class (es)

o ADR, IMDG



Class 3 Flammable liquids 2 Label 3

Packing group

ADR, IMDG

Environmental hazards:

Marine pollutant:
 No

• Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 30

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

Transport category 3

Tunnel restriction code D/E

UN "Model Regulation": UN1268, PETROLEUM PRODUCTS, N.O.S., 3, III

SECTION 15: Regulatory Information

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other Information

 This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal is swallowed and enters airways.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R11 Highly flammable

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.



According to 1907/2006/EC, Article 31

Printing date: 31/05/2013 Version number: 1.0 Revision: 21/01/2013

Trade name: FIX-R Aluminium Paint

Department issuing MSDS: Product safety department

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Éuropean

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

FIX-R Harding Way, St Ives, Cambridgeshire, PE27 3YJ

Tel: 01480 466777 Fax: 01480 290133 Email: info@fix-r.co.uk www.fix-r.co.uk

