

**Product Data Sheet** 

**Application: Built-up Metal Roofs and Walls** 

## **CLADDING ROLL 40**



# Thermal Insulation for Built-up Metal Roofs and Walls

Cladding Roll 40 is a glass mineral wool roll insulation that can be considered for use in builtup metal roofs and walls. The range is supplied in 1.2m wide rolls for quick coverage of large areas. It also reduces the transmission of airborne sound, helping to improve the acoustic comfort of those working within the building.

## **Features and Benefits**



#### **Thermal Performance**

Thermal conductivity of 0.040 W/m.K. Helps to reduce heat loss within the building envelope and decrease energy costs.



### **Fire Classification**

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



#### **Acoustic Benefits**

The fibre structure of glass mineral wool traps sound energy and dissipates it within its thickness, helping to improve the acoustic comfort of those working within the building.



#### Sustainability

Achieves a BRE Green Guide rating of A+ which can assist in demonstrating environmental performance in your BREEAM assessments. Manufactured from up to 75% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit insulation-uk.com/CSR.

# **Key Considerations**

When using ISOVER Cladding Roll 40, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents:

- Declaration of Performance available at insulation-uk.com/products/isover-cladding-roll-40
- Safe Use Instruction Sheet available at insulation-uk.com/healthandsafety

# **Product Specification**

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m²)	Rolls per pallet	Pallet area (m²)	λD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m².K/W)
5200625408	80	10.20	1.20	12.24	24	293.76	0.040	2.00
5200625400	100	8.20	1.20	9.84	24	236.16	0.040	2.50
5200625402	120	6.80	1.20	8.16	24	195.84	0.040	3.00
5200625410	140	5.85	1.20	7.02	24	168.48	0.040	3.50
5200625412	160	5.10	1.20	6.12	24	146.88	0.040	4.00
5200625404	180	4.50	1.20	5.40	24	129.60	0.040	4.50
5200625406	200	4.10	1.20	4.92	24	118.08	0.040	5.00

## **Characteristics**

Thermal	Declared thermal conductivity of 0.040 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.	Certification	UKCA Marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T1.		
Fire	Euroclass A1 Reaction to Fire classification according to EN 13501-1.	Handling, Storage, Health and Safety	Information regarding storage, installation and handling of ISOVER products and health & safety information can be found at insulation-uk.com/healthandsafety.		
Environmental	All ISOVER products are manufactured under Environmental Management System – ISO 14001. BES 6001 Rating "Good" - The Framework Standard for Responsible Sourcing. Please visit insulation-uk.com/ accreditations for further details. Achieves an A+ Green Guide rating for glass mineral wool		Achieves a Eurofins Gold product status for indoor air quality (certificate available at insulation-uk.com/Eurofins) EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit insulation-uk.com/accreditations).		
	insulation ref 815320001 that can assist in demonstrating the environmental performance within BREEAM assessments.	Quality	All ISOVER products are manufactured under Quality Management Standard – ISO 9001. Please visit insulation- uk.com/accreditations for further details		
Recycled Content	Manufactured from up to 75% recycled glass.		anison, assistantians to the details		



### ISOVER

White House Industrial Estate, Runcorn, Cheshire, WA7 3DP

### Customer Service -Order Placement and Enquiries

rei: 01473 820820 Email: iukcustomerservice@saint-gobain.com

### **Technical Support Centre**

Tel: 01473 820850 Email: technicalsupport@saint-gobain.com

### insulation-uk.com

Published date: 08 Feb 2023

ISOVER reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at insulation-uk.com  $\,$ 

Saint-Gobain ISOVER UK Registered in England. Company Number 10442670.

 $Registered\ Offices: Saint-Gobain\ House, East\ Leake,\ Loughborough,\ Leicestershire,\ LE12\ 6JU.$