

Declaration of Performance

No. 112S-DoP2020-07-09

| | | |
|--|--|---|
| 1. Unique identification code of the product-type: | SIGA 112S | |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | 500 x 250mm, 450 x 330mm, 400 x 250mm | |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonized Technical Specification, as foreseen by the manufacturer: | Slate and carbonate slate for discontinuous roofing and cladding | |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): | SIG Roofing Harding Way, St. Ives, Cambridgeshire, PE27 3YJ | |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): | N/A | |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: | AVCP System 4 | |
| 7. Declared Performance | | |
| Essential characteristics | Performance | Harmonised technical specification |
| Dimensional variation | | EN 12326-1:2014 |
| -Nominal thickness | 7mm | |
| -Individual thickness | 7mm (<+/-35%) | |
| -Deviation of length and width | Complies | |
| -Deviation from edge straightness | Complies | |
| -Deviation from rectangularity | Complies | |
| Mechanical resistance (Characteristic modulus of rupture) | Transverse: 34Mpa Longitudinal: 60Mpa | |
| Water absorption | 0.3% Code: W1(≤ 0,6%) | |
| Apparent calcium carbonate | 0.10% (≤ 20%) | |
| Durability: | | |
| -Water absorption | 0,3% Code: W1(≤ 0,6%) | |
| -Freeze-thaw cycling | Not Required | |
| -Thermal cycling | T1 | |
| -Sulfur dioxide exposure | S1 | |
| -Non-carbonate carbon content | 0.6% Complies (≤ 2%) | |
| Release of dangerous substances | None in conditions of use as roofing or external cladding | |
| External fire performance | Deemed to satisfy | |
| Reaction to fire | Deemed to satisfy class A1 | |

8. The performance of the product identified in Points 1 and 2 is in conformity with the declared performance in point.

7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:




Name and function: Philip Johns, Managing Director SIG UK
Place of issue: SIG Roofing, Harding Way, St. Ives, Cambridgeshire, PE27 3YJ
Date of issue: 9/7/2020