

IMPORTED

QUALITY SOFTWOOD TIMBER

SPRUCE & PINE PRODUCTS

PRESSURE TREATED

Traditional Timber Dimensions

UG Sawn

19x38mm 19x50mm 25x38mm 25x50mm

Carcassing UG, C16/24

47x50mm UG 47x75mm C16/24

Carcassing C24

47x100mm 47x125mm 47x150mm 47x175mm

47x200mm 47x225mm 47x250mm

75x100mm 75x150mm 75x200mm 75x225mm

Speciality Timber Dimensions

6x25mm Counterbatten / Plasterboard Lath

11x38mm Counterbatten

12x38mm Drip Batten

50x50mm Corner to Corner (Arris Rail)

50x75mm Corner to Corner (Arris Rail)

50x50mm Mopstick (Lead Roll)



PRODUCT DATA SHEET

- SR Timber "IMPORTED" products are manufactured at our own sawmill as well as carefully selected 3rd party production plants. Timber products should be protected whilst in store to prevent water saturation, this will prevent sagging or twisting of the material.
- SR Timber "IMPORTED" products are available in various lengths ranging from 2.4m up to 5.4m, in 300mm increments. Carcassing is available from 2.4m up to 6.0m in 600mm increments.
- Produced from imported spruce (Whitewood) Abies Alba/Picea abies – WPCA or pine and (Redwood) Pinus sylvestris – PNSY or combined/mixed species – WPPA, all supplied from either FSC® or PEFC™ fully certified or controlled wood resources. All "IMPORTED" products also meet all requirements within EUTR regulations.
- High pressure Tanalith E preservative treated to class 2, as in accordance with recommendations given in BS 8417. All SR Timber "Imported" products carry our standard 60 year service life certification, against insect attack and wood rotting fungi (when used correctly and installed above dpc level in buildings).



SR Timber, Nunn Brook Road
 Huthwaite, Sutton-in-Ashfield
 Nottinghamshire NG17 2HU

Tel: 01623 446800

Fax: 01623 440347

E: sales@sr-timber.co.uk

www.sr-timber.co.uk