



INSTALLATION GUIDE

WIENERBERGER'S LEAD-REPLACEMENT PRODUCT

WARNINGS:

- Do not install if the outside temperature is 5°C or lower.
- Do not install to any substrate with a granular surface*.
- Ensure product is stored indoors where possible prior to installation.
- Undertake any chasing out and clean working area before introducing the Wienerberger lead-replacement product to the area.
- If the flashings are to be left unsecured for any length of time or are subject to strong winds, it is advised that a batten be fixed across the face of the flashing to prevent wind uplift.

KEY MEASUREMENTS:

- Must cover the roof tile by at least 150mm.
- Must extend up any abutments by a minimum of 75mm.
- Must overlap any other Wienerberger lead-replacement product by a minimum of 150mm.
- For any other measurements, please apply standard lead practice as per the LSTA.

PREPARATION:

- Prior to forming the flashing, ensure that surfaces to which it is to be applied are dry and free from any loose debris and dust. Our recommendation is to use a dry cloth to clean the surface. If dust is still present, use a damp cloth to clean the tiles but you must ensure the surface is dry again before applying the flashing.

KEY INSTALL NOTES:

- Before removing the protective liner, gently mould the Wienerberger lead-replacement product to the required shape, ensuring a 50mm overhang of any corner features are achieved.
- Remove the protective backing from the butyl and press the flashing into place onto the masonry and/or roof covering. The flashing can be dressed by hand, but we would strongly recommend using our Wienerberger lead-replacement product dressing tool only to ensure good contact is made with the substrate, especially at the edges.
- Point all flashings into masonry, we recommend doing this last, after adhesion to the substrates is achieved to avoid debris falling onto the butyl.

For further information please refer to our typical CAD details and installation guides/videos. If you have any questions, please contact our technical support team on 0844 9395 999.

**If installation onto a granulated surface is essential, please contact the Sandtoft Technical department on 0844 9395 999.*

Wienerberger Ltd
Wienerberger House,
Brooks Drive
Cheadle Royal Business Park
Cheadle, Cheshire
SK8 3SA

T: 0844 939 5900

